



**Vendor:** Oracle

**Exam Code:** 1Z0-851

**Exam Name:** Java Standard Edition 6 Programmer Certified Professional Exam

**Version:** DEMO

### QUESTION 1

Given a pre-generics implementation of a method:

```
public static int sum(List list) {  
    int sum = 0;  
    for ( Iterator iter = list.iterator(); iter.hasNext(); ) {  
        int i = ((Integer)iter.next()).intValue();  
        sum += i;  
    }  
    return sum;  
}
```

What three changes allow the class to be used with generics and avoid an unchecked warning?  
(Choose three.)

- A. Remove line 14.
- B. Replace line 14 with "int i = iter.next();".
- C. Replace line 13 with "for (int i : intList) {}".
- D. Replace line 13 with "for (Iterator iter : intList) {}".
- E. Replace the method declaration with "sum(List<int> intList)".
- F. Replace the method declaration with "sum(List<Integer> intList)".

**Answer:** ACF

### QUESTION 2

A programmer has an algorithm that requires a java.util.List that provides an efficient implementation of add(0, object), but does NOT need to support quick random access. What supports these requirements?

- A. java.util.Queue
- B. java.util.ArrayList
- C. java.util.LinkedList
- D. java.util.LinearList

**Answer:** D

### QUESTION 3

Given:

```
// insert code here  
private N min, max;  
public N getMin() { return min; }  
public N getMax() { return max; }  
public void add(N added) {  
    if (min == null || added.doubleValue() < min.doubleValue())  
        min = added;  
    if (max == null || added.doubleValue() > max.doubleValue())  
        max = added;  
}
```

}

Which two, inserted at line 11, will allow the code to compile? (Choose two.)

- A. public class MinMax<?> {
- B. public class MinMax<? extends Number> {
- C. public class MinMax<N extends Object> {
- D. public class MinMax<N extends Number> {
- E. public class MinMax<? extends Object> {
- F. public class MinMax<N extends Integer> {

**Answer:** DF

#### QUESTION 4

Given:

```
import java.util.*;  
public class Explorer2 {  
    public static void main(String[] args) {  
        TreeSet<Integer> s = new TreeSet<Integer>();  
        TreeSet<Integer> subs = new TreeSet<Integer>();  
        for(int i = 606; i < 613; i++)  
            if(i%2 == 0) s.add(i);  
        subs = (TreeSet)s.subSet(608, true, 611, true);  
        s.add(629);  
        System.out.println(s + " " + subs);  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. An exception is thrown at runtime.
- C. [608, 610, 612, 629] [608, 610]
- D. [608, 610, 612, 629] [608, 610, 629]
- E. [606, 608, 610, 612, 629] [608, 610]
- F. [606, 608, 610, 612, 629] [608, 610, 629]

**Answer:** E

#### QUESTION 5

Given:

```
public class Score implements Comparable<Score> {  
    private int wins, losses;  
    public Score(int w, int l) { wins = w; losses = l; }  
    public int getWins() { return wins; }  
    public int getLosses() { return losses; }  
    public String toString() {
```

```
return "<" + wins + "," + losses + ">";  
}  
// insert code here  
}
```

Which method will complete this class?

- A. public int compareTo(Object o){/\*more code here\*/}
- B. public int compareTo(Score other){/\*more code here\*/}
- C. public int compare(Score s1,Score s2){/\*more code here\*/}
- D. public int compare(Object o1,Object o2){/\*more code here\*/}

**Answer:** B

### QUESTION 6

Given:

```
public class Person {  
    private name;  
    public Person(String name) {  
        this.name = name;  
    }  
    public int hashCode() {  
        return 420;  
    }  
}
```

Which statement is true?

- A. The time to find the value from HashMap with a Person key depends on the size of the map.
- B. Deleting a Person key from a HashMap will delete all map entries for all keys of type Person.
- C. Inserting a second Person object into a HashSet will cause the first Person object to be removed as a duplicate.
- D. The time to determine whether a Person object is contained in a HashSet is constant and does NOT depend on the size of the map.

**Answer:** A

### QUESTION 7

Given:

```
import java.util.*;  
public class SortOf {  
    public static void main(String[] args) {  
        ArrayList<Integer> a = new ArrayList<Integer>();  
        a.add(1); a.add(5); a.add(3);  
        Collections.sort(a);  
        a.add(2);  
        Collections.reverse(a);  
    }  
}
```

```
System.out.println(a);
}
}
```

What is the result?

- A. [1, 2, 3, 5]
- B. [2, 1, 3, 5]
- C. [2, 5, 3, 1]
- D. [5, 3, 2, 1]
- E. [1, 3, 5, 2]
- F. Compilation fails.
- H. An exception is thrown at runtime.

**Answer:** C

### QUESTION 8

Given

```
public interface Status {
/* insert code here */ int MY_VALUE = 10;
}
```

Which three are valid on line 12? (Choose three.)

- A. final
- B. static
- C. native
- D. public
- E. private
- F. abstract
- G. protected

**Answer:** ABD

### QUESTION 9

Given:

```
class Atom {
Atom() { System.out.print("atom "); }
}
class Rock extends Atom {
Rock(String type) { System.out.print(type); }
}
public class Mountain extends Rock {
Mountain() {
super("granite ");
new Rock("granite ");
}
}
```

```
}

public static void main(String[] a) { new Mountain(); }

}
```


What is the result?

- A. Compilation fails.
- B. atom granite
- C. granite granite
- D. atom granite granite
- E. An exception is thrown at runtime.
- F. atom granite atom granite

**Answer:** F

#### QUESTION 10

Click the Exhibit button. Which three statements are true? (Choose three.)



- A. Compilation fails.
- B. The code compiles and the output is 2.
- C. If lines 16, 17 and 18 were removed, compilation would fail.
- D. If lines 24, 25 and 26 were removed, compilation would fail.

- E. If lines 16, 17 and 18 were removed, the code would compile and the output would be 2.
- F. If lines 24, 25 and 26 were removed, the code would compile and the output would be 1.

**Answer:** BEF

### QUESTION 11

Given:

```
class Line {  
    public class Point { public int x,y; }  
    public Point getPoint() { return new Point(); }  
}  
class Triangle {  
    public Triangle() {  
        // insert code here  
    }  
}
```

Which code, inserted at line 16, correctly retrieves a local instance of a Point object?

- A. Point p = Line.getPoint();
- B. Line.Point p = Line.getPoint();
- C. Point p = (new Line()).getPoint();
- D. Line.Point p = (new Line()).getPoint();

**Answer:** D

### QUESTION 12

Given:

```
class Alpha {  
    public void foo() { System.out.print("Afoo "); }  
}  
public class Beta extends Alpha {  
    public void foo() { System.out.print("Bfoo "); }  
    public static void main(String[] args) {  
        Alpha a = new Beta();  
        Beta b = (Beta)a;  
        a.foo();  
        b.foo();  
    }  
}
```

What is the result?


- A. Afoo Afoo
- B. Afoo Bfoo
- C. Bfoo Afoo
- D. Bfoo Bfoo

- E. Compilation fails.
- H. An exception is thrown at runtime.

**Answer:** D

**QUESTION 13**

Click the Exhibit button. Which statement is true about the classes and interfaces in the exhibit?



- A. Compilation will succeed for all classes and interfaces.
- B. Compilation of class C will fail because of an error in line 2.
- C. Compilation of class C will fail because of an error in line 6.
- D. Compilation of class AImpl will fail because of an error in line 2.

**Answer:** C

**QUESTION 14**

Which two code fragments correctly create and initialize a static array of int elements? (Choose two.)

- A. static final int[] a = { 100,200 };
- B. static final int[] a; static { a=new int[2]; a[0]=100; a[1]=200; }

- C. static final int[] a = new int[2]{ 100,200 };
- D. static final int[] a; static void init() { a = new int[3]; a[0]=100; a[1]=200; }

**Answer:** AB

### QUESTION 15

Given:

```
interface Foo { int bar(); }
public class Sprite {
    public int fubar( Foo foo ) { return foo.bar(); }
    public void testFoo() {
        fubar(
            // insert code here
        );
    }
}
```

Which code, inserted at line 15, allows the class Sprite to compile?

- A. Foo { public int bar() { return 1; } }
- B. new Foo { public int bar() { return 1; } }
- C. new Foo() { public int bar() { return 1; } }
- D. new class Foo { public int bar() { return 1; } }

**Answer:** C

### QUESTION 16

Given:

```
class Alligator {
    public static void main(String[] args) {
        int [][]x[] = {{1,2}, {3,4,5}, {6,7,8,9}};
        int [][]y = x;
        System.out.println(y[2][1]);
    }
}
```

What is the result?

- A. 2
- B. 3
- C. 4
- D. 6
- E. 7
- F. Compilation fails.

**Answer:** E

## Thank You for Trying Our Product

### Braindump2go Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.braindump2go.com/all-products.html>



**10% Discount Coupon Code: BDNT2014**