



**Vendor:** IBM

**Exam Code:** 000-121

**Exam Name:** Virtualization Technical Support for IBMi-V1  
Exam

**Version:** DEMO

### QUESTION 1

What are two methods to determine the partition to which virtual disks are assigned?

- A. In VIO Server, use lspv-AvI  
In the HMC command line, use lsvdev-p
- B. In VIO Server, use lsdev-v command  
In IBM i, use WRKCFRGSTS \*DEV\* VRT
- C. In VIO Server, use the lsctg -vl command  
In IBM i, use the WRKHWDRSC \*STG command
- D. In VIO Server, use the lsmap command  
In the HMC GUI use Virtual Resources/Virtual Storage Management

**Answer: D**

### QUESTION 2

The DSPFMWSTS on an IBM i 7.1 partition appears as shown:

```
itech07.ws
File Edit View Communication Actions Window Help
Display Firmware Status
Service partition . . . . . : No
Firmware update policy . . . . . : *HMC
Server IPL source . . . . . : Temporary
Firmware product ID/release . . . . . : 5733907 V1R1M0

---Server firmware---
Copy      Fix pack      PTF ID
*ACTIVE   AL730_087    MH01310
*TEMP     AL730_087    MH01310
*PERM     AL730_066    MH01299

Bottom

Press Enter to continue
F3=Exit  F5=Refresh  F12=Cancel

M0 A MW 01/001
I902 - Session successfully started
```

As part of troubleshooting, IBM support asks that level AL730\_087 be deactivated.  
How is that accomplished?

- A. Run command DLTPTF PTF(MH01310) RMV(\*TEMP)
- B. Run command RMVPTF LICPGM(5770SS1) SELECT(MH01310) DELAYED(\*YES), then restart the partition
- C. Stop all partitions  
Change the managed system to start in "P" mode  
Restart the managed system  
From the HMC, select Updates
- D. On the resulting screen, select the managed system  
Under Tasks select Change Licensed Internal Code for Current Release In the wizard select Deactivate

Temporary Level

**Answer: C**

**QUESTION 3**

A client IBM i partition running 6.1 is being upgraded to 7.1 using an image catalog on an IBM i 6.1 partition. The image catalog is loaded into a virtual optical device and made available to the client partition using a Network Server Description and virtual SCSI adapters. Which statement is correct?

- A. The next volumes will have to be mounted manually, one by one.
- B. The virtual optical device performs as a library in IBM i 6.1.
- C. The device will show on the client with the same name as on the host.
- D. The virtual optical device should be specified in the NWSD before it can be seen by the client partition.

**Answer: A**

**QUESTION 4**

Auditors have reviewed access to the HMC and determined that many users have too much authority on the HMC. What is the correct method to restrict users to only a specific set of resources?

- A. Change the users' task role to hmcoperator.
- B. Create and assign a new task role that allows only the required set of tasks.
- C. In Manage Users and Tasks, select each resource that is required for this user.
- D. Create and assign a new resource role that allows access to only the required resources.

**Answer: D**

**QUESTION 5**

A client plans to add a Power 770 server to a POWEP6 environment. What resource can the administrator use to determine if the HMC is at the correct level to support the new server firmware?

- A. ASMI
- B. HMC Service Agent
- C. Power Code Matrix
- D. System Planning Tool

**Answer: C**