



Vendor: Cisco

Exam Code: 300-208

Exam Name: Implementing Cisco Secure Access Solutions

Version: DEMO

QUESTION 1

Which devices support download of environmental data and IP from Cisco ISE to SGT bindings in their SGFW implementation?

- A. Cisco ASA devices
- B. Cisco ISR G2 and later devices with ZBFW
- C. Cisco ISR G3 devices with ZBFW
- D. Cisco ASR devices with ZBFW

Answer: A

QUESTION 2

In Cisco ISE 1.3, where is BYOD enabled with dual-SSID onboarding?

- A. client provisioning policy
- B. client provisioning resources
- C. BYOD portal
- D. guest portal

Answer: D

QUESTION 3

Which description of the purpose of the Continue option in an authentication policy rule is true?

- A. It allows Cisco ISE to check the list of rules in an authentication policy until there is a match.
- B. It sends an authentication to the next subrule within the same authentication rule.
- C. It allows Cisco ISE to proceed to the authorization policy regardless of authentication pass/fail.
- D. It sends an authentication to the selected identity store.
- E. It causes Cisco ISE to ignore the NAD because NAD will treat the Cisco ISE server as dead.

Answer: C

QUESTION 4

How many days does Cisco ISE wait before it purges a session from the active session list if no RADIUS Accounting STOP message is received?

- A. 1
- B. 5
- C. 10
- D. 15

Answer: B

QUESTION 5

A user configured a Cisco Identity Service Engine and switch to work with downloadable access list for wired dot1x users, though it is failing to work. Which command must be added to address the issue?

- A. ip dhcp snooping

- B. ip device tracking
- C. dot1x pae authenticator
- D. aaa authentication dot1x default group radius

Answer: B

QUESTION 6

Which option is the correct format of username in MAB authentication?

- A. host/LSB67.cisco.com
- B. chris@cisco.com
- C. 10:41:7F:46:9F:89
- D. CISCO\chris

Answer: C

QUESTION 7

Refer to the exhibit. In a distributed deployment of Cisco ISE, which column in Figure 1 is used to fill in the Host Name field in Figure 2 to collect captures on Cisco ISE while authenticating the specific endpoint?

The screenshot shows the Cisco ISE interface. At the top, there is a table of sessions labeled 'Figure 1'. The table has columns: Time, Status, Details, Repeat Count, Identity, Endpoint ID, Server, Endpoint Profile, Authentication Policy, Authorization Policy, Authorization Profiles, and Network Device. A single row is visible with the following values: 2015-11-11 15:58:29.832, All, a green status icon, a magnifying glass icon, D8:EB:97:86:48:1, D8:EB:97:86:48:88, ise-1-3-pap, WIRELESS, WIRED MAB, WIRED >> Wired MAB, EMPLOYEE-FULL, and Masha-3560c.

Below the table is a 'TCP Dump' configuration window labeled 'Figure 2'. It contains the following fields:

- Status: Stopped (with a red square icon) and a 'Start' button.
- Host Name: ise13admin (dropdown menu)
- Network Interface: GigabitEthernet 0 (dropdown menu)
- Promiscuous Mode: On (radio button selected) and Off (radio button).
- Filter: (empty text box) with an example: 'ip host hellos and not iceberg'
- Format: Raw Packet Data (dropdown menu)

- A. Server
- B. Network Device
- C. Endpoint ID
- D. Identity

Answer: A

QUESTION 8

Which ISE feature is used to facilitate a BYOD deployment?

- A. self-service personal device registration and onboarding
- B. Guest Service Sponsor Portal
- C. Local Web Auth
- D. Guest Identity Source Sequence

Answer: A

QUESTION 9

What are two actions that can occur when an 802.1X-enabled port enters violation mode?
(Choose two.)

- A. The port is error disabled.
- B. The port drops packets from any new device that sends traffic to the port.
- C. The port generates a port resistance error.
- D. The port attempts to repair the violation.
- E. The port is placed in quarantine state.
- F. The port is prevented from authenticating indefinitely.

Answer: AB

QUESTION 10

Which option describes the purpose of configuring Native Supplicant Profile on the Cisco ISE?

- A. It helps employees add and manage new devices by entering the MAC address for the device.
- B. It is used to register personal devices on the network.
- C. It enforces the use of MSCHAPv2 or EAP-TLS for 802.1X authentication.
- D. It provides posture assessments and remediation for devices that are attempting to gain access to the corporate network.

Answer: C

QUESTION 11

Which configuration is required in the Cisco ISE Authentication policy to allow Central Web Authentication?

- A. Dot1x and if authentication failed continue
- B. MAB and if user not found continue
- C. MAB and if authentication failed continue
- D. Dot1x and if user not found continue

Answer: B

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad.**
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER
NETWORKS



EMC²
where information lives®

10% Discount Coupon Code: ASTR14