Vendor: HP

Exam Code: HP0-A20

Exam Name: Install, Maintain and Upgrade NonStop NS-Series Hardware

Version: DEMO

QUESTION 1
Which utility is used to set the IP address in the ServerNet switch board?

A. SCF
B. DSM/SCM
C. Low-level Link
D. OSM Service Connection

Answer: C

QUESTION 2
Which tools are used to evaluate system performance and growth? (Select two.)

A. Measure
B. DSM/TC
C. DSM/SCM
D. OSM Service Connection
E. Tandem Capacity Model (TCM)

Answer: AE

QUESTION 3
When upgrading an existing 8-processor DMR system to a 16-processor DMR system, what is the minimum hardware required?

A. one P-Switch
B. two racks
C. four Blade complexes
D. two Blade complexes

Answer: D

QUESTION 4
Where can you find release-specific fallback information? (Select two.)

A. NonStop eCatalog
B. Total Web Support (TWS)
C. NonStop Technical Library (NTL)
D. Release Version Update (RVU) softdocs
E. Guardian Performance Analyzer (GPA) manual

Answer: CD

QUESTION 5
What is the maximum number of Disk Drive Enclosures (DDEs) that can be daisy-chained together?

A. 3
B. 2

C. 4
D. None

Answer: C

QUESTION 6
Which precautions should be taken before shutting down an NS-series server? (Select two.)

A. Perform a DCOM.
B. Identify current SYSnn.
C. Capture an SCF Snapshot.
D. Execute a SETTIME command.
E. Perform an SCF SAVE CONFIGURATION.

Answer: BE

QUESTION 7
How is Instant Support Enterprise Edition (ISEE) used on NS-series systems? (Select two.)

A. for accessing Scout
B. for sending outbound messages
C. for sending CPU dump files automatically
D. for collecting server configuration modifications
E. for receiving inbound GMCSC support activities

Answer: BE

QUESTION 8
Which cable type connects a NonStop NS16000 system to a 6770 ServerNet Cluster switch?

A. ECL adapter cable
B. multimode fiber optic
C. single-mode fiber optic
D. ServerNet adapter cable

Answer: C

QUESTION 9
Which statement is true regarding an ESD protection kit?

A. It discharges EMF to ground.
B. It connects to any AC power source.
C. It protects people against electrical discharge.
D. It protects components against electrostatic discharge.

Answer: D

QUESTION 10

What input power do NonStop NS16000 Carrier Grade systems require?

A. a single -48 V DC source
B. two separate -48 V DC sources
C. 3-phase 208 V AC, 20 amp source
D. a single-phase 120 V AC, 15 amp source

Answer: B

QUESTION 11
What is the maximum acceptable RMS voltage measured between neutral and ground for powering NonStop NS-series systems?

A. 1
B. 3
C. 5
D. 6

Answer: B

QUESTION 12
What is the maximum allowable length of an MMF cable between a VIO enclosure and a Fibre Channel Disk Module?

A. 25 meters (82 feet)
B. 80 meters (262 feet)
C. 250 meters (820 feet)
D. 400 meters (1312 feet)

Answer: C

QUESTION 13
What is used to replace a SWAN/SWAN2 concentrator?

A. SCF
B. SP Tool
C. WAN Wizard PRO
D. OSM replace action

Answer: A

QUESTION 14
Which component has a specific Check if Safe to Replace OSM action?

A. NonStop Blade Element (NSBE)
B. Gigabit ServerNet Adapter (G4SA)
C. Logical Synchronization Unit (LSU)
D. Fibre Channel Disk Module (FCDM)

Answer: A

QUESTION 15
Which SCF command identifies the location of any disks in a problem state?

A. status disk $*,bad
B. stats disk $*,down
C. control disk $*,sel bad
D. info disk $*,sel not started

Answer: D

Thank You for Trying Our Product

Braindump2go Certification Exam Features:

★ More than 99,900 Satisfied Customers Worldwide.

★ Average 99.9% Success Rate.

★ Free Update to match latest and real exam scenarios.

★ Instant Download Access! No Setup required.

★ Questions & Answers are downloadable in PDF format and VCE test engine format.

★ Multi-Platform capabilities - Windows, Laptop, Mac, Android, iPhone, iPod, iPad.

★ 100% Guaranteed Success or 100% Money Back Guarantee.

★ Fast, helpful support 24x7.

View list of all certification exams: http://www.braindump2go.com/all-products.html

10% Discount Coupon Code: BDNT2014