

Vendor: Juniper

Exam Code: JN0-634

Exam Name: Security, Professional (JNCIP-SEC)

Version: DEMO

QUESTION 1

Your network includes SRX Series devices at the headquarters location. The SRX Series devices at this location are part of a high availability chassis cluster and are configured for IPS. There has been a node failover. In this scenario, which statement is true?

- A. Existing sessions continue to be processed by IPS because of table synchronization.
- B. Existing sessions are no longer processed by IPS and become firewall sessions.
- C. Existing session continue to be processed by IPS as long as GRES is configured.
- D. Existing sessions are dropped and must be reestablished so IPS processing can occur.

Answer: A

QUESTION 2

What are three components of Software-Defined Secure Networks? (Choose three.)

- A. ContrailB. Sky ATP
- B. SRX Series device
- C. Security Director
- D. Network Director

Answer: BCD

QUESTION 3

Which AppSecure feature identifies applications that are present in traffic?

- A. AppIDB. AppTrack
- B. AppFW
- C. AppQoS

Answer: A

QUESTION 4

Which three components are part of the AppSecure services suite? (Choose three.)

- A. IDP
- B. Sky ATP
- C. AppQoS
- D. AppFW
- E. Web filtering

Answer: ACD

QUESTION 5 What is a function of UTM?

- A. AppFW
- B. IPsec
- C. content filtering

D. bridge mode

Answer: C

QUESTION 6

Which two parameters are required to match in an IDP rule for the terminal option to take effect? (Choose two.)

- A. attacks custom-attacks
- B. attacks predefined-attacks
- C. application
- D. source-address

Answer: AB

QUESTION 7

You are implementing user authentication on your network using an SRX Series device and want to ensure that there are redundant forms of authentication for users to access the network. You have configured the device with the integrated user firewall and user role firewall features. You are testing failover methods using the default priority values. In this scenario, which two statements are true? (Choose two.)

- A. If the user fails local authentication, then the Junos OS will attempt to authenticate the user with a user role firewall.
- B. If the user fails user role firewall authentication, then the Junos OS will attempt to authenticate the user with an integrated user firewall.
- C. If the user fails integrated user firewall authentication, then the Junos OS will attempt to authenticate with a user role firewall.
- D. If the user fails local authentication, then the Junos OS will attempt to authenticate the user with an integrated user firewall.

Answer: CD

QUESTION 8

You are configuring transparent mode on an SRX Series device. You must permit IP-based traffic only, and BPDUs must be restarted to the VLANs from which they originate. Which configuration accomplishes these objectives?

- A. bridge {block-non-ip-all;bpdu-vlan-flooding;}
- B. bridge {block-non-ip-all;bypass-non-ip-unicast;no-packet-flooding;}
- C. bridge {bypass-non-ip-unicast;bpdu-vlan-flooding;}
- D. bridge {block-non-ip-all;bypass-non-ip-unicast;bpdu-vlan-flooding;}

Answer: A

★ Instant Download ★ PDF And VCE ★ 100% Passing Guarantee ★ 100% Money Back Guarantee

Thank You for Trying Our Product

Braindump2go Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average 99.9% Success Rate.
- ★ Free Update to match latest and real exam scenarios.
- ★ Instant Download Access! No Setup required.
- ★ Questions & Answers are downloadable in PDF format and VCE test engine format.
- ★ Multi-Platform capabilities Windows, Laptop, Mac, Android, iPhone, iPod, iPad.
- ★ 100% Guaranteed Success or 100% Money Back Guarantee.
- ★ Fast, helpful support 24x7.

View list of all certification exams: <u>http://www.braindump2go.com/all-products.html</u>



10% Discount Coupon Code: BDNT2014

