

**Exam Code:** HP0-239

**Exam Name:** Supporting the Modular Array(MA) Storage  
Family

**Vendor:** HP

**Version:** DEMO

## Part: A

1: Which command is used to view the available utilities offered by the ACS firmware?

- A.LIST
- B.DIRECTORY
- C.VIEW UTILITIES
- D.SHOW UTILITIES

**Correct Answers: B**

2: Which ACS Version is required to run DRM?

- A.8.7D
- B.8.7F
- C.8.7P
- D.8.7S

**Correct Answers: C**

3: In Transparent Failover mode, unit D102 with no preferred path is presented through port \_\_\_\_.

- A.2 on the bottom controller
- B.2 on both controllers
- C.1 on both controllers
- D.1 on the top controller

**Correct Answers: A**

4: An MA8000 has been operating in a single controller configuration. You added a second HSG80 controller for redundancy and started a CLI session through the serial port of the new (lower) controller. Which command do you use to include the new controller into the existing configuration?

- A.SET FAILOVER COPY=THIS\_CONTROLLER
- B.SET MULTIBUS\_FAILOVER=THIS\_CONTROLLER
- C.SET FAILOVER COPY=OTHER\_CONTROLLER
- D.SET MULTIBUS\_FAILOVER=OTHER\_CONTROLLER

**Correct Answers: C**

5: What do you enter at the CLI prompt to configure a CCL (command console LUN) on your HSG80 controller which will be fixed to LUN 0?

- A.SET THIS\_CONTROLLER SCSI\_VERSION=SCSI-2
- B.SET SCSI\_VERSION=SCSI-2
- C.SET D0 SCSI\_VERSION=SCSI-3
- D.SET THIS\_CONTROLLER SCSI\_VERSION=SCSI-3

**Correct Answers: D**

6: You want to remotely configure an HSG80 controller. Before the first remote connection can be established, you must establish a local connection and \_\_\_\_.

- A.create a CCL (command console LUN)

- B.configure the node ID
- C.set the correct time and date
- D.set the correct port topology

**Correct Answers: A**

7: How many HSG controllers are supported in an M2200 enclosure?

- A.2
- B.4
- C.6
- D.22

**Correct Answers: A**

8: Which ACS versions support cloning?

- A.8.7G, 8.7F, 8.7S, 8.7L and 8.7P only
- B.8.7G, 8.7F and 8.7S only
- C.8.7G and 8.7F only
- D.8.7G and 8.7L only

**Correct Answers: A**

9: Which SWCC menu selection sequence is likely to cause customer data loss?

- A.Storage, Controller Configuration, Open
- B.Storage, Controller Configuration, Save
- C.Storage, Controller Configuration, Load
- D.Storage, Controller Configuration, Restart

**Correct Answers: C**

10: A model 4300 drive enclosure with a single power supply contains \_\_\_\_ blowers.

- A.1
- B.2
- C.3
- D.4

**Correct Answers: B**

11: Which utility is used to load a patch for the ACS firmware?

- A.CLCP
- B.FMU
- C.CLONE
- D.CONFIG

**Correct Answers: A**

12: Which cache module does the bottom controller use?

- A.configurable
- B.always left
- C.left only if the right slot is empty

D.always right

**Correct Answers: D**

13: The RA8000 CLI command INITIALIZE initializes \_\_\_\_.

A.metadata only

B.metadata and user data areas

C.user data areas only

D.the NVRAM of the HSG80 controller

**Correct Answers: A**

14: You have connected port 1 of the upper HSG80 controller to an FC switch and opened a terminal session through the serial port of the same controller. Which CLI command do you use to establish the correct topology on port 1?

A.SET PORT\_1 TOPOLOGY=LOOP

B.SET THIS\_CONTROLLER PORT\_1\_TOPOLOGY=FABRIC

C.SET PORT\_1\_TOPOLOGY=FABRIC

D.SET THIS\_CONTROLLER TOPOLOGY=1

**Correct Answers: B**

15: When the CONFIG utility is used after a physical disk was moved from one drive bay to another, the moved disk will be \_\_\_\_.

A.rediscovered and added to the spareset

B.rediscovered and reassigned to the storage set

C.added to the controller configuration with a new name and deleted with the old name

D.added to the controller configuration with a new name and the old name will not be removed from the controller configuration

**Correct Answers: D**