



**Vendor:** Huawei

**Exam Code:** H35-211

**Exam Name:** HCIP-Access V2.0

**Version:** DEMO

**QUESTION 1**

(single) Is the following description correct?

The MAC address consists of 48 bits, usually expressed in 12-digit hexadecimal. The first 6 hexadecimal digits are uniformly distributed by the IEEE to determine the uniqueness of the vendor. The last 6 hexadecimal digits are managed by each vendor.

- A. True
- B. False

**Answer: A**

**QUESTION 2**

(single) By default, how many multicast programs can be viewed by each multicast user under the MA5680T at the same time?

- A. 2
- B. 4
- C. 8
- D. 16

**Answer: C**

**QUESTION 3**

(single) What message in the PPPOE protocol is used to terminate a session?

- A. PADI
- B. PADO
- C. PADS
- D. PADT

**Answer: D**

**QUESTION 4**

(single) Is the following description correct?

In the PPP protocol, after the PPP verification succeeds, the Authenticate phase will be transferred to the Network phase.

- A. True
- B. False

**Answer: A**

**QUESTION 5**

(single) The correct installation method is the prerequisite for ensuring the normal operation of the ONU. Which of the following is the wrong installation method?

- A. Connect the ground wire to the ground bar
- B. Casing protection should be used at the customer line stripping
- C. When the fiber is not in use, it should be covered with a fiber dust cap.

D. Signal lines and power lines should be placed in a centralized manner

**Answer: D**

**QUESTION 6**

(single) Which is the access network voice product in the NGN architecture?

- A. SG
- B. MGC
- C. MG
- D. CSCF

**Answer: C**

**QUESTION 7**

(multiple) Data configuration on the OLT. When adding a Gempport, you usually choose the type of service carried by Gempport.

Which of the following business types does gempport support?

- A. ETH
- B. POTs
- C. TDM
- D. E1

**Answer: AC**

**QUESTION 8**

(single) In the ODN network, how much should the standard range of uplink and downlink optical power attenuation be controlled?

- A. 28.5db, 13db
- B. 13db, 28.5db
- C. 23db, 11db
- D. 11db, 23db

**Answer: B**

**QUESTION 9**

(single) Is the following description correct?

The SIP user identity includes a SIP URL and a TEL URL, either of which can uniquely identify a SIP user. The user ID needs to be configured to be consistent on the MDU and IMS.

- A. True
- B. False

**Answer: A**

## Thank You for Trying Our Product

### Braindump2go Certification Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.braindump2go.com/all-products.html>



**10% Discount Coupon Code: ASTR14**