



Vendor: Network Appliance

Exam Code: NS0-194

Exam Name: NetApp Certified Support Engineer

Version: DEMO

QUESTION 1

For security reasons, you must track the access of files of a specific folder. In this scenario, what should you do to accomplish this task from the storage side?

- A. Implement a Vscan solution.
- B. Use a cron job to save the audit log.
- C. Use role-based access control to track access.
- D. Implement an FPolicy solution.

Answer: D

Explanation:

<https://library.netapp.com/ecmdocs/ECMP1196993/html/GUID-07D368C8-F4DD-4F14-9E68-99C63881EBE7.html>

QUESTION 2

You need to provide a customer an action plan to update an ONTAP system after a security bulletin has been issued.

In this scenario, how do you accomplish this task?

- A. Use the Interoperability Matrix Tool.
- B. Review the ONTAP 9 product page.
- C. Download the target version and do a pre-check.
- D. Use Upgrade Advisor on Active IQ.

Answer: C

QUESTION 3

What is the minimum number of compute nodes required to run the NetApp Deployment Engine for NetApp HCI?

- A. 2
- B. 1
- C. 3
- D. 4

Answer: A

Explanation:

<https://docs.netapp.com/us-en/hci/docs/taskhcgistarted.html#:~:text=The%20minimum%20cluster%20for%20NetApp,to%20all%20NetApp%20HCI%20networks.>

QUESTION 4

Which NetApp technology enables you to perform block-based replication from NetApp Element software to Cloud Volumes ONTAP?

- A. SyncMirror
- B. SnapMirror
- C. Cloud Sync
- D. MetroCluster

Answer: B

QUESTION 5

Referring to the exhibit, which two components should be examined? (Choose two.)

Workload	ID	Latency	Network	Cluster	Data	Disk	QoS	NVRAM	Cloud
-total-		110.35ms	327.00us	327.00us	0ms				
110.02ms	0ms	0ms	0ms						
vs1vol0	111	167.82ms	603.00us	603.00us	0ms				
167.22ms	0ms	0ms	0ms						
vol1	1234	117.76ms	191.00us	191.00us	0ms				
117.56ms	0ms	0ms	0ms						
vol2	999	44.24ms	190.00us	190.00us	0ms	44.05ms	0ms	0ms	0ms
-total-									
38.89ms	256.00us	256.00us	0ms	38.63ms	0ms	0ms	0ms		
vol2	999	64.47ms	266.00us	266.00us	0ms	64.20ms	0ms	0ms	0ms
vol1	1234	27.28ms	253.00us	253.00us	0ms	27.03ms	0ms	0ms	0ms
vs1vol0	111	23.72ms	249.00us	249.00us	0ms	23.47ms	0ms	0ms	0ms
-total-		409.81ms	169.00us	169.00us	0ms				
409.65ms	0ms	0ms	0ms						
vol1	1234	816.92ms	120.00us	120.00us	0ms				
816.80ms	0ms	0ms	0ms						
vol2	999	407.88ms	219.00us	219.00us	0ms				
407.66ms	0ms	0ms	0ms						
vs1vol0	111	3.68ms	193.00us	193.00us	0ms	3.49ms	0ms	0ms	0ms

- A. cluster switches
- B. SAS adapter
- C. network interface card
- D. disk

Answer: BD

QUESTION 6

What are two reasons to use VLANs in a NetApp storage solution? (Choose two.)

- A. to isolate UDP traffic from TCP traffic
- B. to isolate management traffic from other IP traffic
- C. to isolate iSCSI traffic from NAS traffic
- D. to isolate FC traffic from other IP traffic

Answer: AC

QUESTION 7

Which CIFS server configuration determines the domain controllers that a CIFS server uses?

- A. site membership
- B. enabled SMB versions
- C. trusted domains
- D. discovery mode

Answer: A

QUESTION 8

Which three techniques are used in ONTAP to improve storage efficiencies? (Choose three.)

- A. compression
- B. encryption
- C. compaction
- D. ADP
- E. thin provisioning

Answer: ACE

Explanation:

[http //cloud.netapp.com/blog/storage-efficiency-success-stories-with-cloud-volumes-ontap](http://cloud.netapp.com/blog/storage-efficiency-success-stories-with-cloud-volumes-ontap)

QUESTION 9

You are working on a fabric MetroCluster. After a site failure, the plex starts to resync automatically to the aggregate mirror of Aggr1. The plex now shows a status of resyncing. During this process, you experience a slow resync of the SyncMirror plex. In this scenario, how do you solve the problem?

- A. Add more disks to the aggregate to add more I/O capacity.
- B. Destroy and re-create plex, then run a baseline sync.
- C. Tune the resync speed by adding a QoS policy and limit the concurrent I/O to the aggregate.
- D. Tune the resync speed using the storage raid-options command.

Answer: C

Explanation:

<https://library.netapp.com/ecmdocs/ECMP1368831/html/GUID-F3E1536B-0C54-4D4F-B985-3D839032234D.html>

QUESTION 10

When you replace a motherboard, which step will completely test the newly installed component?

- A. From ONTAP, execute sldiag.
- B. From the LOADER prompt, type boot_ontap maint, then execute sldiag.
- C. From the LOADER prompt, type boot_diags, then execute sldiag.
- D. From the LOADER prompt, execute sldiag.

Answer: B

Explanation:

[https://library.netapp.com/ecm/ecm download file/ECMP1199896 \(36\)](https://library.netapp.com/ecm/ecm%20download%20file/ECMP1199896%20(36))

Thank You for Trying Our Product

Braindump2go Certification Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.braindump2go.com/all-products.html>



10% Discount Coupon Code: ASTR14