

Vendor: Huawei

Exam Code: H35-211_V2.5

Exam Name: HCIP-Access V2.5

Version: DEMO



QUESTION 1

Type B protection provides redundant protection for both OLT PON ports and backbone fibers when OLT or OLT PON If the port or trunk fiber fails, manually switch to another - luguang.

A. True

B. False

Answer: B

QUESTION 2

(Radio) When deploying GPON Type C single attribution protection, the following description is correct.

- A. The branch fiber breaks, and the state of the OLT's work port becomes standbY
- B. Two ports protected by the OLT side cannot send and receive data at the same time
- C. When the olt uplink fails, a protection reversal can be triggered
- D. The service configuration of ONU access is completely identical to the configuration before protection

Answer: B

QUESTION 3

The (radio) device periodically sends and receives LMCP packets to avoid information loss, and if packets are not received during () LACp packet interaction cycles, the system considers the port to be down

- A. 3
- B. 5
- C. 4
- D. 2

Answer: A

QUESTION 4

The scope of protection of the (multiple choice) GPON Type B dual attribution protection includes

- A. Primary and standby OLTs
- B. Primary and standby primary thousand fibers
- C. OIT's primary and standby PON should be ports
- D. Primary and standby branch fibers

Answer: ABC

QUESTION 5

When the Type C dual home protection linkage uplink detection, if the OLT or OLT uplink fails, the Type C dual home protection can be reversed to another OLT

A. True



B. False

Answer: A

QUESTION 6

(Single choice) The following statement about defense MAC Spoofing is wrong

- A. MAC Anti- Mac Spoofing' features are mutually exclusive with WMAC, SC, PPPOE SMAC features at the VLA level
- B. After the anti-MAC Spoofing function is enabled, the system automatically implements the dynamic binding of the AC address to the service flow
- C. After enabling the Anti-MAC Spoofing function, for IPoE users using fixed IP, the user needs to be statically configured
- D. Turning off the Anti-MAC Spoofing function can only take out the fixed table items, which does not affect the user's service application, but the service forwarding surface will be interrupted.

Answer: D

QUESTION 7

(Multiple choice) When the OLT main control board CPU is detected to be continuously elevated, the following possible causes are?

- A. The user logged in illegally
- B. Network loops
- C. Cyber attacks
- D. Rogue ONU

Answer: BCD

QUESTION 8

(Single choice) The following statement about the PITP protocol is incorrect

- A. The PITP protocol includes pitp P mode and PITP V mode
- B. The purpose of the PITP feature is to provide the upper authentication server with the physical location information of the access user, and the BRAS device can realize the user account and the press position after obtaining the user access location information
- C. Bind the authentication of the information to avoid the theft and roaming of the user account
- D. In pitp V mode, the user's physical location information is added to the PPPOE message sent by the user side to cooperate with the upper-level server for user authentication
- E. PITP P mode can also be called PPOE+ mode

Answer: D

QUESTION 9

(Single choice) In GPON systems, in order to prevent network monitoring, the most common method is.

- A. Information encryption
- B. Physical transport (not networked)



- C. Cableless network transmission
- D. Use leased line transmission

Answer: A

QUESTION 10

(Radio) When the 0LT global or VLAN service template enables the PITP switch, the service port allows the upstream packet to be carried, the Vendor tag switch, and the user to carry the vendor upstream packet In the case of tarf information, the following statement regarding olts to PITP message processing strategies is correct

- A. OLT adds a local Vendor tap to the upstream PITP packet
- B. OLT forwards the USER-side PITP message directly without any processing
- C. OIT is left with the Vendor tag carried in the upstream PITP message, plus the local Vendor tag
- D. OLT drops upstream PITP packets

Answer: C

QUESTION 11

(Single choice) The following statement about ssH connection is incorrect, yes

- A. ssH can be applied to remote encryption of encrypted file transfers over remote encryption connections
- B. The ssH protocol encrypts all transmitted data, effectively preventing information leakage problems during remote management
- C. From a client perspective, SSH provides two levels of security authentication.
- D. The ssH protocol is working at the network layer

Answer: D

QUESTION 12

(Radio) The following is not the QOS service model, is

- A. Diffserv
- B. Intserv
- C. FIFO service
- D. Best Effort

Answer: A



Thank You for Trying Our Product

Braindump2go Certification Exam Features:

- ★ More than 99,900 Satisfied Customers Worldwide.
- ★ Average 99.9% Success Rate.
- ★ Free Update to match latest and real exam scenarios.
- ★ Instant Download Access! No Setup required.
- ★ Questions & Answers are downloadable in PDF format and VCE test engine format.
- ★ Multi-Platform capabilities Windows, Laptop, Mac, Android, iPhone, iPod, iPad.
- ★ 100% Guaranteed Success or 100% Money Back Guarantee.
- ★ Fast, helpful support 24x7.

View list of all certification exams: http://www.braindump2go.com/all-products.html

























10% Discount Coupon Code: ASTR14





