Vendor: F5

Exam Code: 303

Exam Name: F5 ASM Specialist

Version: DEMO

QUESTION 1
An LTM Specialist needs to gather website statistics such as latency and throughput on the existing virtual server. This virtual server load Balances the backend web servers. Which F5 feature will provide this?

A. the Performance panel
B. the AVR module
C. the Dashboard
D. the Statistics panel

Answer: B

QUESTION 2
Which Standard Virtual Server settings should an LTM Specialist use to load balance across routed path of two different ISPs?

A. address translation enabled and port translation disabled
B. both address and port translation enabled
C. both address and port translation disabled
D. address translation disabled and port translation enabled

Answer: B

QUESTION 3
An LTM Specialist needs to terminate client SSL traffic and based on the cookie presented by client. Which set of profiles should the LTM Specialist use?

A. HTTPS, Client SSL, Cookie Persistence Profile
B. HTTP, Server SSL, SSL Cookie Profile
C. HTTPS, Server SSL, SSL Cookie Profile
D. HTTP, Client SSL, Cookie Persistence Profile,

Answer: D

QUESTION 4
A VCMP guest has the following characteristics:

```
- Resources allocated for CPU memory, network interfaces, and disk
space
- Virtual disk created
- The guest is NOT running
```

The guest is NOT running in which state is the VCMP guest

A. Offline
B. Deployed
C. Provisioned
D. Configured

Answer: C

QUESTION 5
An LTM Specialist regularly provides analytics reports that show that traffic generated by different subnets within the organization. The LTM Specialist needs show the associate department names next the IP addresses in the reports. Which step should the LTM Specialist take to meet this requirement?

A. use an iRule to change the output of the report
B. export the report and add the department names manually
C. create VLANs for each subnet and set the name accordingly
D. define active subnets and assign a name to certain subnets

Answer: C

QUESTION 6
In which Application Visibility and Reporting (AYR) profile must the SMTP profile be defined to configure notifications via email?

A. App analytics profile
B. virtual server profile
C. custom analytics profile
D. default analytics profile

Answer: C

QUESTION 7
An LTM Specialist needs to provide access to a 8BG-IP to device for a company's support person access to the BIG IP device, but are NOT allowed to change any settings All support the support remote access to the BIG-IP device, but are NOT allowed to change ant settings. All support have accounts in the company's Active Directory. Which method is appropriate to provide access for the support personnel to the BIG-JP device?

A. configure remote authentication for all users with a default user role of Guest
B. configure remote authentication and map support personnel users to the Guest user role
C. configure remote authentication and map support personnel users to the Operator user role
D. configure remote authentication for all users with a default user role of Operator

Answer: B

QUESTION 8
An LTM Specialist needs to load balance an application using an LTM device to meet the requirements:

```
- The application servers do NOT Support SSL, but client access to the
application should be secured.
- Multiple requests from the same client should be sent to the same
pool member.
- All pool members will have roughly the same processing power, and
traffic should be distributed evenly.
- The LTM device is NOT the pool members' default gateway.
```

Which configuration should the LTM Specialist?

A. a performance 14 virtual server with a SNAT and cookie persistence
B. a performance L4 virtual server with a Client SSL profile and Source Address persistence
C. A performance L4 virtual server with a SNAT, HTTP profile. Server SSL profile, and cookie persistence
D. A standard virtual server with a SNAT, HTTP profile Server SSL profile, and cookie persistence
E. A standard virtual server with a SNAT, HTTP profile, Client profile, andd cookie persistance.

Answer: E

QUESTION 9
Remote users who access the LTM device are authenticated via Radius. The default remote user role is Guest Some users need LTM device with the Administrator role. The F5 Radius attributes are configure on the Radius server. Which configuration item needs to be created?

A. Remote User role
B. Admin account
C. User role
D. User account

Answer: A

QUESTION 10
A pool with a default connection limit is configured to use Round Robin as the load balancing method. An LTM Specialist needs to ensure that the LTM device selects a server with the fewest number of connections when new clients connect. Another pool is using the same set of backend servers. Which load balancing-method should the pool be changed to?

A. Weighted Least Connections (node]
B. Weighted Least Connections (member)
C. Least Connections
D. Least Connections

Answer: C

QUESTION 11
An LTM device needs an additional traffic group. Which configuration item is required?

A. Default device
B. Group name
C. MAC Masquerade Address
D. Auto Fallback Timeout

Answer: B

QUESTION 12
A new HITP server has been deployed on an LTM device. The application running on the server

must be monitored by the LIM device. The following is required:

```
- When the server is unavailable, it will send an HTTP status code of
200 in response to a request for the status html page.
- When the server is available. I will send and HTTP status code of 201
in response to a request for the status html page.
- When the 200 status code is received, the pool member should receive
No new connections.
```

Which configuration change should be made to meet these requirements?

A. set the Send String to GET/ status html and the Receive String to 200 and Receive Disable String to 201.
B. set the Send String to GET Arian and the Receive String to 200 and Receive Disable String to 201.
C. set the Send String to GET Arian and the Receive Disable String to 200 and Receive String to 201.
D. set the Send String to Get /status html and the Receive Disable String to 200 and Receive String to 201.

Answer: D

QUESTION 13
Which two profiles should be used on the virtual server? (Choose two.)

```
set payload {CACHE :: payload}
}
```

A. http-transparent
B. http compression
C. http
D. webacceleration
E. stream

Answer: CD

QUESTION 14
A design requires the LTM device to become HA standby when the one of the two physical interface on the External trunk is down the External trunk is an interface on the External VLAN. Which TMOS command enables this behavior?

A. tmsh modify net van External failsafe enabled
B. tmsh create sys ha-group External trunks add Externally
C. tmsh create sys ha-group External trunks add External threshold 2 weight 101)
D. tmsh create sys ha-group External trunks add (External(attribute percent up-members 100))

Answer: C

Thank You for Trying Our Product

Braindump2go Certification Exam Features:

★ More than **99,900** Satisfied Customers Worldwide.

★ Average **99.9%** Success Rate.

★ **Free Update** to match latest and real exam scenarios.

★ **Instant Download** Access! No Setup required.

★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.

★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.

★ **100%** Guaranteed Success or **100%** Money Back Guarantee.

★ **Fast**, helpful support **24x7**.

View list of all certification exams: http://www.braindump2go.com/all-products.html

10% Discount Coupon Code: **ASTR14**