

Exam Code: e20-350

Exam Name: networked storage-san implementation
exam

Vendor: EMC

Version: DEMO

Part: A

- 1: Which main sets of input are captured using SAN Architect?
- A.Zoning Requirements, Storage Arrays, Topologies
 - B.Servers and Storage Requirements, Performance, Topologies
 - C.Servers and Storage Requirements, Storage Arrays, Topologies
 - D.Servers and Storage Requirements, Storage Arrays, Device masking

Correct Answers: C

- 2: What is the purpose of Auto-Port Assignment in SAN Architect?
- A.Virtual Fabric Creation
 - B.Auto matrix qualification
 - C.Reassign all fabric connections in a highly available fashion
 - D.Reassign only the connections that are NOT highly available

Correct Answers: C

- 3: Which tool provides a visual representation of SAN and DAS designs for SAN Architect?
- A.Visio
 - B.Word
 - C.HTML
 - D.PowerPoint

Correct Answers: A

- 4: Which tasks are performed using SAN Architect?
- A.Design, Model and Validate
 - B.Documentation, masking and Zoning lists
 - C.Statement of work, Project plan and Sales order
 - D.Part numbers, serial numbers and cable diagrams

Correct Answers: A

- 5: What is one of EMC's recommendations for zoning in a B-series?
- A.Hard zoning
 - B.Mixed zoning
 - C.Single HBA zoning
 - D.Aliases for zone members

Correct Answers: C

- 6: Which event causes a fabric rebuild in a B-Series fabric?
- A.cfgenable
 - B.Hard zoning
 - C.Fabric Manager
 - D.Switch/Director removed

Correct Answers: D

7: What is a valid range of Domain IDs in interopmode for B-Series Switch/Directors?

- A.0-31
- B.1-239
- C.97-127
- D.128-239

Correct Answers: C

8: What happens when Zoning Security is enabled in Fabric Manager?

- A.Zoning only per serial connection
- B.No zoning changes are permitted
- C.Access zoning only with the primary fibre channel switch
- D.Zoning is permitted from all switches with dedicated passwords

Correct Answers: C

9: How many IP addresses are needed for installing an ED-12000B director?

- A.2
- B.4
- C.6
- D.8

Correct Answers: B

10: What is the setting for creating a serial connection to a B-Series Switch/Director?

- A.2400, parity
- B.2400, no parity
- C.9600, parity
- D.9600, no parity

Correct Answers: A

11: What is EMC's recommended maximum number of hops between two B-series Switch/Directors?

- A.2
- B.3
- C.4
- D.5

Correct Answers: B

12: Which fibre channel feature automatically determines routing in a multi-switch fabric?

- A.FSPF
- B.Routing
- C.Spanning Tree
- D.ISL Aggregation

Correct Answers: A

13: Click the Task button.

Match the methods on the right for monitoring a fabric with the protocols on the left.

Match the methods on the right for monitoring a fabric with the protocols on the left.

Protocols	Methods
SNMP	(place label here)
HTTP	(place label here)
Serial	(place label here)
Telnet	(place label here)

Console
Framework
Web Server
Command Line

Correct Answers:

Match the methods on the right for monitoring a fabric with the protocols on the left.

Protocols	Methods
SNMP	Framework
HTTP	Web Server
Serial	Console
Telnet	Command Line

Console
Framework
Web Server
Command Line

14: Which type of cable is needed when connecting to a B-Series Switch/Director maintenance port using a hyper-terminal?

- A. Cross over cable
- B. Null Modem cable
- C. 10/100 Ethernet cable
- D. Pass through serial cable

Correct Answers: D

15: Which B-Series model allows non-disruptive firmware upgrades running firmware 4.1.x?

- A. DS-16B
- B. DS-16B2
- C. DS-16B3
- D. ED-12000B

Correct Answers: D