

➤ **Vendor: Cisco**

➤ **Exam Code: 010-151**

➤ **Exam Name: Supporting Cisco Data Center System Devices**

➤ **New Updated Questions from Braindump2go (Updated in August/2020)**

**Visit Braindump2go and Download Full Version 010-151 Exam Dumps**

**QUESTION 87**

What is the name of the process to automatically upgrade a new Fabric Interconnect when it is connected to the functioning Fabric Interconnect?

- A. Firmware Policy Process
- B. Auto-Negotiate Process
- C. Auto-Sync Process
- D. Firmware Update Process

**Answer: D**

**QUESTION 88**

Which tool is needed when servicing a UCS M5 server?

- A. PCIe slot cover
- B. T-30 Torx driver
- C. M5 DIMM puller
- D. HDD removal tool

**Answer: B**

**QUESTION 89**

When replacing a standalone C-Series server which order will be used to shut down the server via CIMC?

- A. Click Power off, Click Shut off
- B. Click Power off, Click Shut down
- C. Click Host power, Click Shut off
- D. Click Host power, Click Shut down

**Answer: B**

**QUESTION 90**

Which command syntax is correct to reset the admin password when the switch is in the kickstart prompt? switch(boot)#"

- A. exec -> admin-password
- B. connect local-mgmt -> admin-password
- C. configure terminal -> admin-password
- D. connect nxos -> admin-password <password>
- E. admin-password

**[010-151 Exam Dumps](#) [010-151 Exam Questions](#) [010-151 PDF Dumps](#) [010-151 VCE Dumps](#)**

**<https://www.braindump2go.com/010-151.html>**

**Answer: C**

**QUESTION 91**

Which statement about the Cisco Nexus 3408-S switch is true?

- A. It is offered in a three-rack-unit (3-RU) form factor.
- B. It supports 200G or 400G line card expansion modules.
- C. It has dual-redundant power supplies.
- D. It is 4-slot chassis with 400G line card expansion modules.

**Answer: C**

**QUESTION 92**

What enables NVM Express host software to communicate with nonvolatile memory?

- A. SATA
- B. SAS
- C. PCIe
- D. SCSI

**Answer: C**

**QUESTION 93**

Which two transceivers can support 100 Gigabit Ethernet? (Choose two.)

- A. SFP+
- B. SFP28
- C. QSFP+
- D. QSFP28
- E. SFP-DD

**Answer: CD**

**QUESTION 94**

What are two common steps to troubleshooting a rack server with unrecognized or memory errors? (Choose two.)

- A. Ensure DIMMs are installed in correct slots
- B. Check CPU sockets for bent pins
- C. Check that the AC power cord is OK
- D. Reseat DIMMs
- E. Check the front I/O cable connection to the motherboard

**Answer: AD**

**QUESTION 95**

Which Cisco UCS Virtual Interface Card Series is designed exclusively for the M5 generation?

- A. M81KR VIC
- B. VIC 1400 Series
- C. VIC 1300 Series
- D. VIC 1200 Series

**Answer: B**

**QUESTION 96**

When activating the firmware via UCSM which two firmware versions must be activated at the same time?

- A. UCS Manager and System
- B. UCS Manager and Kernel
- C. CIMC and Kernel
- D. System and Kernel

**Answer: D**

**QUESTION 97**

In Cisco UCS C480 M5 server, which PCIe slot is the default slot for the rear RAID controller when the rear drive module is used with SAS/SATA drives?

- A. PCIe slot 09
- B. PCIe slot 10
- C. PCIe slot 11
- D. PCIe slot 12

**Answer: C**