

➤ **Vendor: Cisco**

➤ **Exam Code: 300-415**

➤ **Exam Name: Implementing Cisco SD-WAN Solutions (ENSDWI)**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Jan/2021](#))**

Visit Braindump2go and Download Full Version 300-415 Exam Dumps

QUESTION 16

Which value is verified in the certificates to confirm the identity of the device?

- A. Serial Number
- B. OTP
- C. System-IP
- D. Chassis-ID

Answer: A

QUESTION 17

Which hardware component is involved in the Cisco SD-WAN authentication process for ISR platforms?

- A. ZTP
- B. OTPC
- C. SUDI
- D. TPMD

Answer: C

QUESTION 18

Which component of the Cisco SD-WAN architecture oversees the control plane of overlay network to establish, adjust, and maintain the connections that form the Cisco SD-WAN fabric?

- A. APIC-EM
- B. vSmart
- C. vManage
- D. vBond

Answer: B

Explanation:

<https://www.cisco.com/c/dam/en/us/td/docs/routers/sdwan/migration-guide/cisco-sd-wan-migration-guide.pdf>

QUESTION 19

Which two hardware platforms support Cisco IOS XE SD-WAN images? (Choose two.)

- A. ISR4000 series
- B. ISR9300 series
- C. vEdge-1000 series
- D. ASR9000 series

[300-415 Exam Dumps](#) [300-415 Exam Questions](#) [300-415 PDF Dumps](#) [300-415 VCE Dumps](#)

<https://www.braindump2go.com/300-415.html>

E. ASR1000 series

Answer: AE

Explanation:

https://www.cisco.com/c/en/us/solutions/collateral/enterprise-networks/sd-wan/white_paper-c11-741071.html

QUESTION 20

What is a default protocol for control plane connection?

- A. HTTPS
- B. TLS
- C. IPsec
- D. DTLS

Answer: D

Explanation:

https://sdwan-docs.cisco.com/Product_Documentation/Software_Features/SD-WAN_Release_16.3/05Security/02Configuring_Security_Parameters

QUESTION 21

Which component of the Cisco SD-WAN control plane architecture should be located in a public Internet address space and facilitates NAT-traversal?

- A. WAN Edge
- B. vSmart
- C. vBond
- D. vManage

Answer: C

Explanation:

https://www.cisco.com/c/dam/global/da_dk/assets/pdfs/cisco_virtual_update_cisco_sdwan_viptela.pdf

QUESTION 22

Which Cisco SD-WAN WAN Edge platform supports LTE and Wi-Fi?

- A. ISR 1101
- B. ASR 1001
- C. CSR 1000v
- D. vEdge 2000

Answer: A

QUESTION 23

Refer to the exhibit. What does the BFD value of 8 represent?

Hostname	State	System IP	Reachability	Site ID	Device Model	BFD	Control
 BR1-VEGE1		10.3.0.1	reachable	300	vEdge Cloud	8	5

- A. dead timer of BFD session
- B. poll-interval of BFD session
- C. hello timer of BFD session
- D. number of BFD sessions

Answer: D

QUESTION 24

Which command disables the logging of syslog messages to the local disk?

- A. no system logging disk local
- B. system logging server remote
- C. no system logging disk enable
- D. system logging disk disable

Answer: C

Explanation:

https://sdwan-docs.cisco.com/Product_Documentation/Software_Features/SD-WAN_Release_16.3/02System_and_Interfaces/08Configuring_System_Logging

QUESTION 25

Which platforms are managed by a single vManage dashboard?

- A. ISR4351, ASR1002HX, vEdge2000, vEdge Cloud
- B. ISR4321, ASR1001, Nexus, ENCS
- C. ISR4321, ASR1001, ENCS, ISRv
- D. ISR4351, ASR1009, vEdge2000, CSR1000v

Answer: C

Explanation:

<https://www.cisco.com/c/dam/en/us/solutions/collateral/enterprise-networks/sd-wan/nb-06-sw-defined-wan-faq-cte-en.pdf>

QUESTION 26

Which alarm setting is configured to monitor serious events that affect, but do not shut down, the operation of a network function?

- A. Critical
- B. Medium
- C. Major
- D. Minor

Answer: C

Explanation:

https://sdwan-docs.cisco.com/Product_Documentation/vManage_How-Tos/Troubleshooting/Monitor_Alarms

QUESTION 27

Which pathway under Monitor > Network > Select Device is used to verify service insertion configuration?

- A. System Status
- B. Troubleshooting
- C. Real Time
- D. Events

Answer: C

Explanation:

<https://www.ciscolive.com/c/dam/r/ciscolive/apjc/docs/2018/pdf/LABEN-2010-LG.pdf>

QUESTION 28

What is the default interval for BFD packets?

- A. 1 second
- B. 15 seconds

- C. 10 seconds
- D. 5 seconds

Answer: A

QUESTION 29

Which two options are SD-WAN solution capabilities? (Choose two.)

- A. Ability to provide and integrate security with complementary products and applications
- B. The separation of management plane, control plane and data plane to enable horizontal scaling
- C. Truck roll branch turn up for easy provisioning and new installations
- D. Cloud hosted or on-Premise fully redundant management and control plane functions

Answer: BD

QUESTION 30

Which two platforms for the Cisco SD-WAN architecture are deployable in a hypervisor on-premises or in IAAS Cloud? (Choose two.)

- A. CSR 1000v
- B. ISR 4431
- C. vEdge 100c
- D. vEdge 2000
- E. vEdge Cloud

Answer: AE

Explanation:

<https://www.cisco.com/c/dam/en/us/solutions/collateral/enterprise-networks/sd-wan/nb-06-cisco-sd-wan-ebook-cte-en.pdf>

QUESTION 31

How is the scalability of the Manage increased in Cisco SD-WAN Fabric?

- A. Increase the bandwidth of the WAN link connected to the vManage
- B. Increase licensing on the vManage
- C. Deploy more than one vManage controllers on different physical server
- D. Deploy multiple vManage controllers in a cluster

Answer: D

QUESTION 32

Which component of the Cisco SD-WAN control plane architecture facilitates the storage of certificates and configurations for network components?

- A. vSmart
- B. WAN Edge
- C. vManage
- D. vBond

Answer: C

Explanation:

<https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/sdwan-xe-gs-book/system-overview.html>