

➤ **Vendor: Cisco**

➤ **Exam Code: 300-620**

➤ **Exam Name: Implementing Cisco Application Centric Infrastructure**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Sep/2020](#))**

[Visit Braindump2go and Download Full Version 300-620 Exam Dumps](#)

QUESTION 56

What are two of the three methods in integrating the Cisco ACI with existing network infrastructure? (Choose two.)

- A. as a super cloud overseeing a subcloud
- B. as a data center policy engine
- C. as a network supervisor module
- D. as an additional data center pod
- E. as an atomic network operator

Answer: BD

QUESTION 57

Assuming that a service device you are integrating into the Cisco ACI is dedicated to one tenant, where should you configure the logical device and associated concrete devices?

- A. within the tenant context
- B. in the device's base hypervisor UI
- C. within the management tenant
- D. on the service device itself

Answer: A

QUESTION 58

Which three networking architectures is the Cisco ACI architecture based on? (Choose three.)

- A. leaf-and-spine architecture
- B. multicast gateway
- C. a controller that is not involved in traffic forwarding
- D. software-based mapping database lookup
- E. zero-touch provisioning for all loopbacks, Layer 3 links, and routing within the fabric
- F. Host-based forwarding in the mapping database that provides IP-to-VLAN tunnel endpoint mapping information to the spine

Answer: ACE

QUESTION 59

Which new construct must a user create when configuring in-band management?

- A. VLAN pool
- B. management contract
- C. management tenant
- D. bridge domain

Answer: D

Explanation:

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/apic/sw/kb/b_KB_Configuring_Static_Management_Access.html

QUESTION 60

What must be configured to allow SNMP traffic on the APIC controller?

- A. out-of-band management interface
- B. contract under tenant mgmt
- C. SNMP relay policy
- D. out-of-band bridge domain

Answer: B

QUESTION 61

Which type of port is used for in-band management within ACI fabric?

- A. spine switch port
- B. APIC console port
- C. leaf access port
- D. management port


[300-620 Exam Dumps](#) [300-620 Exam Questions](#) [300-620 PDF Dumps](#) [300-620 VCE Dumps](#)

<https://www.braindump2go.com/300-620.html>

Answer: C

QUESTION 62

Refer to the exhibit. A client reports that the ACI domain connectivity to the fiber channel storage is experiencing a B2B credit oversubscription. The environment has a SYSLOG server for state collection messages. Which value should be chosen to clear the critical fault?



Edit Stats Threshold

transmit B2B credit cumulative

Normal Value: 300

Threshold Direction: Both Rising Falling

Rising Thresholds to Config: ☒ Critical ☐ Major ☐ Minor ☒ Warning

Rising

	Set	Reset
Critical	500	
Major		
Minor		
Warning	400	300

- A. 300
- B. 410
- C. 350
- D. 510

Answer: B

QUESTION 63

Which statement about ACI syslog is true?

- A. Notifications for different scopes of syslog objects can be sent only to one destination.
- B. Syslog messages are sent to the destination through the spine.
- C. All syslog messages are sent to the destination through APIC.
- D. Switches send syslog messages directly to the destinations.

Answer: A

Explanation:

<https://www.ciscolive.com/c/dam/r/ciscolive/us/docs/2016/pdf/BRKACI-2303.pdf>

QUESTION 64

A data center administrator is upgrading an ACI fabric. There are 3 APIC controllers in the fabric and all the servers are dual-homed to pairs of leaf switches configured in VPC mode. How should the fabric be upgraded to minimize possible traffic impact during the upgrade?

- A.
 1. Create two maintenance groups for the APIC controllers: VPC left and VPC right.
 2. Upgrade the first group of controllers.
 3. Upgrade the second group of controllers.
 4. Upgrade the leaf switches.
- B.
 1. Create two maintenance groups for APIC controllers: VPC left and VPC right.
 2. Upgrade the leaf switches.
 3. Upgrade the first group of controllers.
 4. Upgrade the second group of controllers.
- C.
 1. Create two maintenance groups for the leaf switches: VPC left and VPC right.
 2. Upgrade the APIC controllers.
 3. Upgrade the first group of leaf switches.
 4. Upgrade the second group of leaf switches.
- D.
 1. Create two maintenance groups for the leaf switches: VPC left and VPC right.
 2. Upgrade the first group of switches.
 3. Upgrade the second group of switches.
 4. Upgrade the APIC controllers.

Answer: D

QUESTION 65

Which protocol does ACI use to securely save the configuration in a remote location?

- A. SCP
- B. HTTPS

[300-620 Exam Dumps](https://www.braindump2go.com) [300-620 Exam Questions](https://www.braindump2go.com) [300-620 PDF Dumps](https://www.braindump2go.com) [300-620 VCE Dumps](https://www.braindump2go.com)

<https://www.braindump2go.com/300-620.html>

- C. TFTP
- D. FTP

Answer: A

Explanation:

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/apic/sw/kb/b_KB_Using_Import_Export_to_Recover_Config_States.html

QUESTION 66

Which two protocols support accessing backup files on a remote location from the APIC? (Choose two.)

- A. TFTP
- B. FTP
- C. SFTP
- D. SMB
- E. HTTPS

Answer: BC

Explanation:

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/apic/sw/1-x/troubleshooting/b_APIC_Troubleshooting/b_APIC_Troubleshooting_appendix_010011.html