

➤ **Vendor:** Cisco➤ **Exam Code:** 300-625➤ **Exam Name:** Implementing Cisco Storage Area Networking (DCSAN)➤ **New Updated Questions from** [Braindump2go](#) **(Updated in** [April/2020](#)**)****Visit Braindump2go and Download Full Version 300-625 Exam Dumps****QUESTION 12**

What is the effect of a non-graceful virtual machine shutdown on a virtualized server that is connected to a SAN with Fibre Channel interfaces?

- A. NP Port reload connected to the upstream SAN switch
- B. out-of-service Fibre Channel interfaces on the SAN switch
- C. frames stuck in the storage system
- D. frames stuck in the HBA buffer of the server

Correct Answer: B**QUESTION 13**

Which condition requires using a device alias rather than a Fibre Channel alias?

- A. The zone database must be distributed over the fabric.
- B. The same alias must be used in zoning as well as DPVM.
- C. All aliases being used are being configured in the same VSAN.
- D. Aliases must be saved within a central database on the fabric.

Correct Answer: A**QUESTION 14**

Which result occurs if a device alias is renamed and then the original device alias name is used in an **add** command in the same session?

- A. Both commands execute successfully.
- B. The device alias is renamed and the **add** command is moved to the rejected list.
- C. Both commands are moved to the rejected list.
- D. The **rename** command is moved to the rejected list and the **add** command executes successfully.

Correct Answer: A

QUESTION 15

Which result occurs when a VSAN is deleted that contains non-trunking ports?

- A. The ports are moved to VSAN 4094.
- B. The ports are moved to VSAN 1.
- C. The ports are removed from the configuration.
- D. The port configurations are cleared.

Correct Answer: A

QUESTION 16

DRAG DROP

Drag and drop the FLOGI parameters from the left onto the descriptions from which they were-derived on the right.

Select and Place:

fWWN	VSAN-based sWWN of the NPV device
IP address	IP address of the NPV device
symbolic node name	fWWN of the F Port on the NPV core switch
nWWN	NPV switch name
pWWN	fWWN of the NP Port

Correct Answer:

fWWN	nWWN
IP address	IP address
symbolic node name	fWWN
nWWN	symbolic node name
pWWN	pWWN

QUESTION 17

A storage network engineer is implementing a port channel for multiple FCIP interfaces with write acceleration in a client's storage network. Which channel mode must be used?

- A. on
- B. passive
- C. active
- D. force

Correct Answer: C

QUESTION 18

A storage administrator wants to enable NPV in a Fibre Channel edge switch. Which configuration is supported in this mode?

- A. Cisco Fabric Services distribution over Fibre Channel
- B. E Port connectivity to the core switch
- C. local switching of east-west traffic
- D. Dynamic Port VSAN Membership

Correct Answer: A

QUESTION 19

Which configuration is always required when running the setup utility on a Cisco MDS 9000 Series Switch?

- A. administrator password
- B. management IP address
- C. active NTP server
- D. active default gateway

Correct Answer: A

QUESTION 20

A network engineer is configuring a Cisco MDS switch for FCoE. Which two conditions must be considered during the implementation phase? (Choose two.)

- A. On Cisco MDS switches, system-defined class maps for class-FCoE and class-default are enabled but can be deleted.
- B. The QoS policy must be identical to other Cisco FCoE switches in the network.
- C. On the Cisco MDS, the MTU is set equal to 2112.
- D. VLAN 1 or the native VLAN can be mapped to an FCoE VSAN.
- E. FCoE is already enabled on a Cisco MDS switch.

Correct Answer: BE

QUESTION 21

Which port mode is used on an NPV device to connect to an NPIV core switch?

- A. E
- B. F
- C. N
- D. NP

Correct Answer: D

QUESTION 22

A storage administrator is configuring inter-VSAN routing on a fabric that contains duplicate domain IDs. Which feature must be configured to ensure continued operation?

- A. auto topology
- B. transit VSANs
- C. IVR NAT
- D. virtual domains

Correct Answer: C