

➤ **Vendor:** Cisco➤ **Exam Code:** 300-625➤ **Exam Name:** Implementing Cisco Storage Area Networking (DCSAN)➤ **New Updated Questions from** [Braindump2go](#) (Updated in [April/2020](#))**Visit Braindump2go and Download Full Version 300-625 Exam Dumps****QUESTION 16****DRAG DROP**

Drag and drop the FLOGI parameters from the left onto the descriptions from which they were-derived on the right.

Select and Place:

fWWN	VSAN-based sWWN of the NPV device
IP address	IP address of the NPV device
symbolic node name	fWWN of the F Port on the NPV core switch
nWWN	NPV switch name
pWWN	fWWN of the NP Port

Correct Answer:

fWWN	nWWN
IP address	IP address
symbolic node name	fWWN
nWWN	symbolic node name
pWWN	pWWN

QUESTION 17

A storage network engineer is implementing a port channel for multiple FCIP interfaces with write acceleration in a client's storage network. Which channel mode must be used?

- A. on
- B. passive
- C. active
- D. force

Correct Answer: C**QUESTION 18**

A storage administrator wants to enable NPV in a Fibre Channel edge switch. Which configuration is supported in this mode?

- A. Cisco Fabric Services distribution over Fibre Channel
- B. E Port connectivity to the core switch
- C. local switching of east-west traffic
- D. Dynamic Port VSAN Membership

Correct Answer: A**QUESTION 19**

Which configuration is always required when running the setup utility on a Cisco MDS 9000 Series Switch?

- A. administrator password
- B. management IP address
- C. active NTP server
- D. active default gateway

Correct Answer: A**QUESTION 20**

[300-625 Exam Dumps](#) [300-625 Exam Questions](#) [300-625 PDF Dumps](#) [300-625 VCE Dumps](#)

[https://www.braindump2go.com/300-625.html`](https://www.braindump2go.com/300-625.html)

A network engineer is configuring a Cisco MDS switch for FCoE. Which two conditions must be considered during the implementation phase? (Choose two.)

- A. On Cisco MDS switches, system-defined class maps for class-FCoE and class-default are enabled but can be deleted.
- B. The QoS policy must be identical to other Cisco FCoE switches in the network.
- C. On the Cisco MDS, the MTU is set equal to 2112.
- D. VLAN 1 or the native VLAN can be mapped to an FCoE VSAN.
- E. FCoE is already enabled on a Cisco MDS switch.

Correct Answer: BE

QUESTION 21

Which port mode is used on an NPV device to connect to an NPIV core switch?

- A. E
- B. F
- C. N
- D. NP

Correct Answer: D

QUESTION 22

A storage administrator is configuring inter-VSAN routing on a fabric that contains duplicate domain IDs. Which feature must be configured to ensure continued operation?

- A. auto topology
- B. transit VSANs
- C. IVR NAT
- D. virtual domains

Correct Answer: C

QUESTION 23

Which EtherType is used by the FCoE Initialization Protocol?

- A. 0x8913
- B. 0x8914
- C. 0xxfc0e D.
- 0x8906

Correct Answer: B

QUESTION 24

What is the function of the 0xFFFFFC address in a Fibre Channel fabric?

- A. management server
- B. fabric controller
- C. name server
- D. time server

Correct Answer: C

QUESTION 25

Refer to the exhibit.

```
switch# (config) interface fcip 51
switch# (config) use-profile 10
switch# (config) peer-info ipaddr 10.1.1.1
switch# (config) no shutdown

switch# show fcip profile 10
FCIP Profile 10
Internet Address is 10.0.0.10 (interface GigabitEthernet1/0)
Listen Port is 3225
TCP parameters
SACK is disabled
PMTU discovery is enabled, reset timeout is 3600 sec
Keep alive is 60 sec
Minimum retransmission timeout is 300 ms
Maximum number of re-transmissions is 4
Send buffer size is 0 KB
Maxumum allowed bandwidth is 1000000 kbps
Minimum available bandwidth is 15000 kbps
Estimated round trip time is 1000 usec
```

Which configuration change improves the ability of the link to recover from frame loss?

- A. Increase the reset timeout.
- B. Enable selective acknowledgment.
- C. Increase the send buffer size to 15000 KB.
- D. Disable PMTU discovery.

Correct Answer: B

QUESTION 26

An engineer is configuring a SAN environment and attempts to activate a zoneset, but a lock is held by another user. Which argument does the engineer use to clear the lock from the zoning database configuration?

- A. commit
- B. abort
- C. clear
- D. force

Correct Answer: C