

➤ **Vendor: Cisco**

➤ **Exam Code: 300-710**

➤ **Exam Name: Securing Networks with Cisco Firepower (SNCF)**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Nov./2020](#))**

**[Visit Braindump2go and Download Full Version 300-710 Exam Dumps](#)**

#### **QUESTION 1**

Which CLI command is used to control special handling of ClientHello messages?

- A. system support ssl-client-hello-tuning
- B. system support ssl-client-hello-display
- C. system support ssl-client-hello-force-reset
- D. system support ssl-client-hello-reset

**Answer: A**

#### **QUESTION 2**

Which command is typed at the CLI on the primary Cisco FTD unit to temporarily stop running high-availability?

- A. configure high-availability resume
- B. configure high-availability disable
- C. system support network-options
- D. configure high-availability suspend

**Answer: B**

#### **QUESTION 3**

Which command must be run to generate troubleshooting files on an FTD?

- A. system support view-files
- B. sudo sf\_troubleshoot.pl
- C. system generate-troubleshoot all
- D. show tech-support

**Answer: B**

#### **QUESTION 4**

When do you need the file-size command option during troubleshooting with packet capture?

- A. when capture packets are less than 16 MB
- B. when capture packets are restricted from the secondary memory
- C. when capture packets exceed 10 GB
- D. when capture packets exceed 32 MB

**Answer: D**

**[300-710 Exam Dumps](#) [300-710 Exam Questions](#) [300-710 PDF Dumps](#) [300-710 VCE Dumps](#)**

**<https://www.braindump2go.com/300-710.html>**

**QUESTION 5**

What is a functionality of port objects in Cisco FMC?

- A. to mix transport protocols when setting both source and destination port conditions in a rule
- B. to represent protocols other than TCP, UDP, and ICMP
- C. to represent all protocols in the same way
- D. to add any protocol other than TCP or UDP for source port conditions in access control rules.

**Answer: B**

**QUESTION 6**

Within Cisco Firepower Management Center, where does a user add or modify widgets?

- A. dashboard
- B. reporting
- C. context explorer
- D. summary tool

**Answer: A**

**QUESTION 7**

A network engineer is configuring URL Filtering on Firepower Threat Defense. Which two port requirements on the Firepower Management Center must be validated to allow communication with the cloud service? (Choose two.)

- A. outbound port TCP/443
- B. inbound port TCP/80
- C. outbound port TCP/8080
- D. inbound port TCP/443
- E. outbound port TCP/80

**Answer: AE**

**QUESTION 8**

What is the maximum bit size that Cisco FMC supports for HTTPS certificates?

- A. 1024
- B. 8192
- C. 4096
- D. 2048

**Answer: D**

**QUESTION 9**

Which limitation applies to Cisco Firepower Management Center dashboards in a multidomain environment?

- A. Child domains can view but not edit dashboards that originate from an ancestor domain.
- B. Child domains have access to only a limited set of widgets from ancestor domains.
- C. Only the administrator of the top ancestor domain can view dashboards.
- D. Child domains cannot view dashboards that originate from an ancestor domain.

**Answer: D**

**QUESTION 10**

Which two statements about deleting and re-adding a device to Cisco FMC are true? (Choose two.)

**[300-710 Exam Dumps](#) **[300-710 Exam Questions](#) [300-710 PDF Dumps](#) [300-710 VCE Dumps](#)****

**<https://www.braindump2go.com/300-710.html>**

- A. An option to re-apply NAT and VPN policies during registration is available, so users do not need to re-apply the policies after registration is completed.
- B. Before re-adding the device in Cisco FMC, you must add the manager back in the device.
- C. No option to delete and re-add a device is available in the Cisco FMC web interface.
- D. The Cisco FMC web interface prompts users to re-apply access control policies.
- E. No option to re-apply NAT and VPN policies during registration is available, so users need to re-apply the policies after registration is completed.

**Answer:** DE

#### **QUESTION 11**

What is a behavior of a Cisco FMC database purge?

- A. User login and history data are removed from the database if the User Activity check box is selected.
- B. Data can be recovered from the device.
- C. The appropriate process is restarted.
- D. The specified data is removed from Cisco FMC and kept for two weeks.

**Answer:** C

#### **QUESTION 12**

Which two packet captures does the FTD LINA engine support? (Choose two.)

- A. Layer 7 network ID
- B. source IP
- C. application ID
- D. dynamic firewall importing
- E. protocol

**Answer:** BE

#### **QUESTION 13**

Which two features of Cisco AMP for Endpoints allow for an uploaded file to be blocked? (Choose two.)

- A. application blocking
- B. simple custom detection
- C. file repository
- D. exclusions
- E. application whitelisting

**Answer:** AB

#### **QUESTION 14**

Which action should you take when Cisco Threat Response notifies you that AMP has identified a file as malware?

- A. Add the malicious file to the block list.
- B. Send a snapshot to Cisco for technical support.
- C. Forward the result of the investigation to an external threat-analysis engine.
- D. Wait for Cisco Threat Response to automatically block the malware.

**Answer:** A

#### **QUESTION 15**

[300-710 Exam Dumps](#) [300-710 Exam Questions](#) [300-710 PDF Dumps](#) [300-710 VCE Dumps](#)

<https://www.braindump2go.com/300-710.html>

Which Cisco Advanced Malware Protection for Endpoints policy is used only for monitoring endpoint actively?

- A. Windows domain controller
- B. audit
- C. triage
- D. protection

**Answer: B**

**QUESTION 16**

What is a valid Cisco AMP file disposition?

- A. non-malicious
- B. malware
- C. known-good
- D. pristine

**Answer: B**

**QUESTION 17**

In a Cisco AMP for Networks deployment, which disposition is returned if the cloud cannot be reached?

- A. unavailable
- B. unknown
- C. clean
- D. disconnected

**Answer: A**

**QUESTION 18**

Which two remediation options are available when Cisco FMC is integrated with Cisco ISE? (Choose two.)

- A. dynamic null route configured
- B. DHCP pool disablement
- C. quarantine
- D. port shutdown
- E. host shutdown

**Answer: CD**

**QUESTION 19**

Which connector is used to integrate Cisco ISE with Cisco FMC for Rapid Threat Containment?

- A. pxGrid
- B. FTD RTC
- C. FMC RTC
- D. ISEGrid

**Answer: A**

**QUESTION 20**

What is the maximum SHA level of filtering that Threat Intelligence Director supports?

- A. SHA-1024
- B. SHA-4096

- C. SHA-512
- D. SHA-256

**Answer: D**