

# Braindump2go Guarantee All Exams 100% Pass One Time!

Vendor: Cisco

> Exam Code: 300-710

- **Exam Name:** Securing Networks with Cisco Firepower (SNCF)
- ➤ New Updated Questions from <u>Braindump2go</u> (Updated in <u>Nov./2020</u>)

### Visit Braindump2go and Download Full Version 300-710 Exam Dumps

### **QUESTION 21**

**Drag and Drop Question** 

Drag and drop the steps to restore an automatic device registration failure on the standby Cisco FMC from the left into the correct order on the right. Not all options are used.

Enter the "configure manager add" command at the CLI of the affected device.	Step 1
Unregister the device from the standby Cisco FMC.	Step 2
Register the affected device on the active Cisco FMC.	Step 3
Enter the "configure manager delete" command at the CLI of the affected device.	Step 4
Register the affected device on the standby Cisco FMC.	
Unregister the device from the active Cisco FMC.	

Answer:



# **Braindump2go Guarantee All Exams 100% Pass**

**One Time!** 

Unregister the device from the standby Cisco FMC.

Unregister the device from the active Cisco FMC.

Enter the "configure manager delete" command at the CLI of the affected device.

Enter the "configure manager add" command at the CLI of the affected device.

Register the affected device on the active Cisco FMC.

Register the affected device on the standby Cisco FMC.

### **QUESTION 22**

With Cisco FirePOWER Threat Defense software, which interface mode do you configure to passively receive traffic that passes the appliance?

- A. transparent
- B. routed
- C. passive
- D. inline set
- E. inline tap

### Answer: C

### **QUESTION 23**

Which description of a correlation policy configuration in the Cisco Firepower Management Center is true?

- A. The system displays correlation policies that are created on all of the domains in a multidomain deployment
- B. Deleting a response group deletes the responses of that group
- C. You cannot add a host profile qualification to a correlation rule that is triggered by a malware
- D. Correlation policy priorities override whitelist priorities

### Answer: C

### **QUESTION 24**

What is a result of enabling Cisco FTD clustering?

- A. For the dynamic routing feature, if the master unit fails, the newly elected master unit maintains all existing connections.
- B. Integrated Routing and Bridging is supported on the master unit.
- C. Site-to-site VPN functionality is limited to the master unit, and all VPN connections are dropped if the master unit fails.
- D. All Firepower appliances can support Cisco FTD clustering.

Answer: C

300-710 Exam Dumps 300-710 Exam Questions 300-710 PDF Dumps 300-710 VCE Dumps



### Braindump2go Guarantee All Exams 100% Pass

**One Time!** 

### **QUESTION 25**

Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: AE

### **QUESTION 26**

On the advanced tab under inline set properties, which allows interfaces to emulate a passive interface?

- A. transparent inline mode
- B. TAP mode
- C. strict TCP enforcement
- D. propagate link state

Answer: D

### **QUESTION 27**

What are the minimum requirements to deploy a managed device inline?

- A. inline interfaces, security zones, MTU, and mode
- B. passive interface, MTU, and mode
- C. inline interfaces, MTU, and mode
- D. passive interface, security zone, MTU, and mode

Answer: C

### **QUESTION 28**

What is the difference between inline and inline tap on Cisco Firepower?

- A. Inline tap mode can send a copy of the traffic to another device.
- B. Inline tap mode does full packet capture.
- C. Inline mode cannot do SSL decryption.
- D. Inline mode can drop malicious traffic.

Answer: D

### **QUESTION 29**

With Cisco Firepower Threat Defense software, which interface mode must be configured to passively receive traffic that passes through the appliance?

- A. inline set
- B. passive
- C. routed
- D. inline tap

Answer: B

### **QUESTION 30**

Which two deployment types support high availability? (Choose two.)

300-710 Exam Dumps 300-710 Exam Questions 300-710 PDF Dumps 300-710 VCE Dumps



# **Braindump2go Guarantee All Exams 100% Pass**

**One Time!** 

- A. transparent
- B. routed
- C. clustered
- D. intra-chassis multi-instance
- E. virtual appliance in public cloud

Answer: AB

### **QUESTION 31**

What are 2 types or forms of suppression on a FirePower policy (or FTD)?

- A. source
- B. port
- C. rule
- D. protocol
- E. application

Answer: AC