

➤ **Vendor: Cisco**

➤ **Exam Code: 300-710**

➤ **Exam Name: Securing Networks with Cisco Firepower (SNCF)**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Nov./2020](#))**

[Visit Braindump2go and Download Full Version 300-710 Exam Dumps](#)

QUESTION 32

Which two dynamic routing protocols are supported in FirePower Threat Defense v6.0? (Choose Two)

- A. IS-IS
- B. BGP
- C. OSPF
- D. static routing
- E. EIGRP

Answer: BC

QUESTION 33

Which protocol establishes network redundancy in a switched Firepower device deployment?

- A. STP
- B. HSRP
- C. GLBP
- D. VRRP

Answer: A

QUESTION 34

Which interface type allows packets to be dropped?

- A. passive
- B. inline
- C. ERSPAN
- D. TAP

Answer: B

QUESTION 35

Which Cisco Firepower Threat Defense, which two interface settings are required when configuring a routed interface? (Choose two.)

- A. Redundant Interface
- B. EtherChannel
- C. Speed
- D. Media Type

[300-710 Exam Dumps](#) [300-710 Exam Questions](#) [300-710 PDF Dumps](#) [300-710 VCE Dumps](#)

<https://www.braindump2go.com/300-710.html>

E. Duplex

Answer: CE

QUESTION 36

Which two dynamic routing protocols are supported in Firepower Threat Defense without using FlexConfig? (Choose two.)

- A. EIGRP
- B. OSPF
- C. static routing
- D. IS-IS
- E. BGP

Answer: CE

QUESTION 37

Which policy rule is included in the deployment of a local DMZ during the initial deployment of a Cisco NGFW through the Cisco FMC GUI?

- A. a default DMZ policy for which only a user can change the IP addresses.
- B. deny ip any
- C. no policy rule is included
- D. permit ip any

Answer: C

QUESTION 38

What are two application layer preprocessors? (Choose two.)

- A. CIFS
- B. IMAP
- C. SSL
- D. DNP3
- E. ICMP

Answer: BC

QUESTION 39

Which two OSPF routing features are configured in Cisco FMC and propagated to Cisco FTD? (Choose two.)

- A. OSPFv2 with IPv6 capabilities
- B. virtual links
- C. SHA authentication to OSPF packets
- D. area boundary router type 1 LSA filtering
- E. MD5 authentication to OSPF packets

Answer: BD

QUESTION 40

With Cisco FirePOWER Threat Defense software, which interface mode do you configure for an IPS deployment, where traffic passes through the appliance but does not require VLAN rewriting?

- A. inline set
- B. passive

- C. inline tap
- D. routed
- E. transparent

Answer: D

QUESTION 41

What Software can be installed on the Cisco 4100 series appliance? (Choose two)

- A. FTD
- B. ASA
- C. ASAv
- D. FMC

Answer: AB

QUESTION 42

Which two field can be used to create a new email alert within the Cisco Firepower Management center under Policies > Actions > Alerts tab? (Choose two.)

- A. Device
- B. Source
- C. Destination
- D. From
- E. Relay Host

Answer: DE

QUESTION 43

When creating a report template, how can the results be limited to show only the activity of a specific subnet?

- A. Create a custom search in Firepower Management Center and select it in each section of the report.
- B. Add an Input Parameter in the Advanced Settings of the report, and set the type to Network/IP.
- C. Add a Table View section to the report with the Search field defined as the network in CIDR format.
- D. Select IP Address as the X-Axis in each section of the report.

Answer: B