

➤ **Vendor: Cisco**

➤ **Exam Code: 300-715**

➤ **Exam Name: Implementing and Configuring Cisco Identity Services Engine (SISE)**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Nov.2020](#))**

[Visit Braindump2go and Download Full Version 300-715 Exam Dumps](#)

QUESTION 73

What are the three default behaviors of Cisco ISE with respect to authentication, when a user connects to a switch that is configured for 802.1X, MAB, and WebAuth? (Choose three)

- A. MAB traffic uses internal endpoints for retrieving identity.
- B. Dot1X traffic uses a user-defined identity store for retrieving identity.
- C. Unmatched traffic is allowed on the network.
- D. Unmatched traffic is dropped because of the Reject/Reject/Drop action that is configured under Options.
- E. Dot1 traffic uses internal users for retrieving identity.

Answer: ADE

QUESTION 74

Which statement is true?

- A. A Cisco ISE Advanced license is perpetual in nature.
- B. A Cisco ISE Advanced license can be installed on top of a Base and/or Wireless license.
- C. A Cisco ISE Wireless license can be installed on top of a Base and/or Advanced license.
- D. A Cisco ISE Advanced license can be used without any Base licenses.

Answer: B

QUESTION 75

In which scenario does Cisco ISE allocate an Advanced license?

- A. guest services with dACL enforcement
- B. endpoint authorization using SGA enforcement
- C. dynamic device profiling
- D. high availability Administrator nodes

Answer: C

QUESTION 76

Which Cisco ISE node does not support automatic failover?

- A. Inline Posture node
- B. Monitoring node

[300-715 Exam Dumps](#) [300-715 Exam Questions](#) [300-715 PDF Dumps](#) [300-715 VCE Dumps](#)

<https://www.braindump2go.com/300-715.html>

- C. Policy Services node
- D. Admin node

Answer: D

QUESTION 77

Which scenario does not support Cisco ISE guest services?

- A. wired NAD with local WebAuth
- B. wireless LAN controller with central WebAuth
- C. wireless LAN controller with local WebAuth
- D. wired NAD with central WebAuth

Answer: B

QUESTION 78

By default, which traffic does an 802.1X-enabled switch allow before authentication?

- A. all traffic
- B. no traffic
- C. traffic permitted in the port dACL on Cisco ISE
- D. traffic permitted in the default ACL on the switch

Answer: D

QUESTION 79

What does MAB leverage a MAC address for?

- A. Calling-Station-ID
- B. password
- C. cisco-av-pair
- D. username

Answer: D

QUESTION 80

Which three conditions can be used for posture checking? (Choose three.)

- A. certificate
- B. operating system
- C. file
- D. application
- E. service

Answer: CDE

QUESTION 81

Which use case validates a change of authorization?

- A. An authenticated, wired EAP-capable endpoint is discovered
- B. An endpoint profiling policy is changed for authorization policy.
- C. An endpoint that is disconnected from the network is discovered
- D. Endpoints are created through device registration for the guests

Answer: B

[300-715 Exam Dumps](#) [300-715 Exam Questions](#) [300-715 PDF Dumps](#) [300-715 VCE Dumps](#)

<https://www.braindump2go.com/300-715.html>

Explanation:

https://www.cisco.com/c/en/us/td/docs/security/ise/1-2/user_guide/ise_user_guide/ise_prof_pol.html

QUESTION 82

An administrator is adding a switch to a network that is running Cisco ISE and is only for IP Phones. The phones do not have the ability to auto switch port for authentication?

- A. enable bypass-MAC
- B. dot1x system-auth-control
- C. mab
- D. enable network-authentication

Answer: B

QUESTION 83

A network engineer is configuring a network device that needs to filter traffic based on security group tags using a security policy on a routed into this task?

- A. cts authorization list
- B. cts role-based enforcement
- C. cts cache enable
- D. cts role-based policy priority-static

Answer: B