

➤ **Vendor: Cisco**

➤ **Exam Code: 300-715**

➤ **Exam Name: Implementing and Configuring Cisco Identity Services Engine (SISE)**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Nov.2020](#))**

[Visit Braindump2go and Download Full Version 300-715 Exam Dumps](#)

QUESTION 84

An engineer is working with a distributed deployment of Cisco ISE and needs to configure various network probes to collect a set of attributes from the used to accomplish this task?

- A. policy service
- B. monitoring
- C. pxGrid
- D. primary policy administrator

Answer: B

QUESTION 85

An engineer is configuring Cisco ISE to reprofile endpoints based only on new requests of INIT-REBOOT and SELECTING message types. Which probe should be used to accomplish this task?

- A. MMAP
- B. DNS
- C. DHCP
- D. RADIUS

Answer: C

QUESTION 86

An engineer is using Cisco ISE and configuring guest services to allow wireless devices to access the network. Which action should accomplish this task?

- A. Create the redirect ACL on the WLC and add it to the WLC policy
- B. Create the redirect ACL on the WLC and add it to the Cisco ISE policy.
- C. Create the redirect ACL on Cisco ISE and add it to the WLC policy
- D. Create the redirect ACL on Cisco ISE and add it to the Cisco ISE Policy

Answer: B

QUESTION 87

An engineer is configuring web authentication using non-standard ports and needs the switch to redirect traffic to the correct port. Which command should be used to accomplish this task?

- A. permit tcp any any eq <port number>

[300-715 Exam Dumps](#) [300-715 Exam Questions](#) [300-715 PDF Dumps](#) [300-715 VCE Dumps](#)

<https://www.braindump2go.com/300-715.html>

- B. aaa group server radius proxy
- C. ip http port <port number>
- D. aaa group server radius

Answer: C

QUESTION 88

An administrator needs to connect ISE to Active Directory as an external authentication source and allow the proper ports through the firewall. Which two ports should be opened to accomplish this task? (Choose two)

- A. TELNET 23
- B. LDAP 389
- C. HTTP 80
- D. HTTPS 443
- E. MSRPC 445

Answer: BE

QUESTION 89

Refer to the exhibit. A network engineers configuring the switch to accept downloadable ACLs from a Cisco ISC server. Which two commands should be run to complete the configuration? (Choose two)

```
Switch(config)# aaa new-model  
Switch(config)# aaa authentication dot1x default group radius  
Switch(config)# aaa authorization network default group radius
```

- A. aaa authorization auth-proxy default group radius
- B. radius server vsa send authentication
- C. radius-server attribute 8 include-in-access-req
- D. ip device tracking
- E. dot1x system-auth-control

Answer: BC

QUESTION 90

An engineer is using the low-impact mode for a phased deployment of Cisco ISE and is trying to connect to the network prior to authentication. Which access will be denied in this?

- A. HTTP
- B. DNS
- C. EAP
- D. DHCP

Answer: A

QUESTION 91

A network engineer needs to ensure that the access credentials are not exposed during the 802.1x authentication among components. Which two protocols should complete this task?

- A. PEAP
- B. EAP-MD5
- C. LEAP
- D. EAP-TLS

E. EAP-TTLS

Answer: BD

QUESTION 92

An engineer is configuring a guest password policy and needs to ensure that the password complexity requirements are set to mitigate brute force attacks. Which two requirement complete this policy? (Choose two)

- A. minimum password length
- B. active username limit
- C. access code control
- D. password expiration period
- E. username expiration date

Answer: AD

QUESTION 93

Which two actions occur when a Cisco ISE server device administrator logs in to a device? (Choose two)

- A. The device queries the internal identity store
- B. The Cisco ISE server queries the internal identity store
- C. The device queries the external identity store
- D. The Cisco ISE server queries the external identity store.
- E. The device queries the Cisco ISE authorization server

Answer: AD

QUESTION 94

When planning for the deployment of Cisco ISE, an organization's security policy dictates that they must use network access authentication via RADIUS. It also states that the deployment provide an adequate amount of security and visibility for the hosts on the network. Why should the engineer configure MAB in this situation?

- A. The Cisco switches only support MAB.
- B. MAB provides the strongest form of authentication available.
- C. The devices in the network do not have a supplicant.
- D. MAB provides user authentication.

Answer: C

QUESTION 95

In a Cisco ISE split deployment model, which load is split between the nodes?

- A. AAA
- B. network admission
- C. log collection
- D. device admission

Answer: A

Explanation:

https://www.cisco.com/c/en/us/td/docs/security/ise/2-6/install_guide/b_ise_InstallationGuide26.pdf