

➤ **Vendor: Cisco**

➤ **Exam Code: 350-601**

➤ **Exam Name: Implementing and Operating Cisco Data Center Core Technologies (DCCOR)**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Sep/2020](#))**

Visit Braindump2go and Download Full Version 350-601 Exam Dumps

QUESTION 1

An engineer is seeking the most optimal on demand CPU performance while configuring the BIOS settings of a UCS C-series rack mount server.

What setting will accomplish this goal?

- A. C6 Retention
- B. C6 non-Retention
- C. C2 state
- D. C0/C1 state

Answer: A

QUESTION 2

An engineer is duplicating an existing Cisco UCS setup at a new site.

What are two characteristics of a logical configuration backup of a Cisco UCS Manager database? (Choose two.)

- A. contains the configured organizations and locales
- B. contains the VLAN and VSAN configurations
- C. contains the AAA and RBAC configurations
- D. contains all of the configurations
- E. contains a file with an extension tgz that stores all of the configurations

Answer: BC

QUESTION 3

A Cisco MDS 9000 Series Storage Switch has reloaded unexpectedly.

Where does the engineer look for the latest core dump file?

- A. /mnt/recovery
- B. /mnt/core
- C. /mnt/logs
- D. /mnt/pss

Answer: D

QUESTION 4

An engineer must implement a Cisco UCS system at a customer site. One of the requirements is to implement SAN boot. The storage system maps the source WWPN to a unique LUN.

Which method does Cisco recommend to configure the SAN boot?

- A. Define the vHBAs as bootable and leave the boot target definition empty.
- B. Create a SAN boot policy in which every initiator is mapped to a different target LUN.
- C. Define the vHBAs as bootable and leave the default values on the boot target definition.
- D. Create a SAN boot policy in which every initiator is mapped to the same target LUN.

Answer: D

QUESTION 5

In an FCoE environment, for which two sets of data must an interface that implements the PAUSE mechanism always provision sufficient ingress buffer? (Choose two.)

- A. frames that were sent with high credit
- B. frames that were sent on the link but not yet received
- C. frames that were processed and transmitted by the transmitter after the PAUSE frame left the sender
- D. frames that were processed and transmitted by the transmitter before the PAUSE frame left the sender
- E. frames that were sent on the link and received

Answer: BD

QUESTION 6


What are two types of FC/FCoE oversubscription ratios? (Choose two.)

- A. switch processing power to end-node processing power
- B. port bandwidth to uplink bandwidth
- C. server storage to end-node count
- D. edge ISL bandwidth to core ISL bandwidth
- E. host bandwidth to storage bandwidth

Answer: DE

QUESTION 7

Refer to the exhibit. An engineer is implementing zoning on two Cisco MDS switches. After the implementation is finished, E Ports that connect the two Cisco MDS switches become isolated.



What is wrong with the implementation?

- A. Zones are local to the MDS switch and name service must be used to activate the connection between E Ports.
- B. Different zone set names must be configured on both MDS switches.
- C. Zones must have the same name on both MDS switches for the E Ports to function.
- D. E Ports on both MDS switches must be configured as F Ports for the zoning to function.

Answer: A

QUESTION 8

An engineer is implementing NPV mode on a Cisco MDS 9000 Series Switch. Which action must be taken?

- A. NPIV must be enabled on the upstream switch.
- B. The FCNS database must be disabled in the fabric.
- C. A port channel must be configured to the upstream switch.
- D. All switches in the fabric must be Cisco MDS switches.

Answer: A

QUESTION 9

Which two statements about modifying Cisco UCS user accounts are true? (Choose two.)

- A. Disabling a user account maintains all of the data in the Cisco UCS Fabric Interconnect.
- B. The admin account can be used to log on by using SSH only.
- C. The password of the user account must contain a minimum of 10 characters.
- D. Local user accounts override the same account on a remote authentication server, such as TACACS, RADIUS, or LDAP.
- E. The password of the user account expires in 30 days.

Answer: AD

QUESTION 10

An engineer must ensure fabric redundancy when implementing NPV mode on a Cisco MDS 9000 Series Switch. Which action enables fabric redundancy?

- A. Use TE ports to connect to upstream switches.
- B. Add a port channel to upstream switches.
- C. Configure the NPV devices to use an external FLOGI database.
- D. Connect the NPV devices to multiple upstream switches.

Answer: B

Section: (none)

Explanation/Reference:

Explanation:

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/mds9000/sw/5_0/configuration/guides/int/nxos/cli_interface_s/pc.html

QUESTION 11

An engineer is converting a Cisco MDS switch to support NPIV mode. What should be considered when implementing the solution?

- A. It requires mapping of external interface traffic.
- B. It must be enabled on VSAN 1 only.
- C. It must be enabled globally on all VSANs.

D. It requires the FLOGI database to be disabled.

Answer: C

QUESTION 12

Refer to the exhibit. What is the result of implementing this configuration?

```
N5K-1(config)#interface fc2/3
N5K-1(config-if)#switchport mode sd
N5K-1(config-if)# no shutdown
```

- A. The Fibre Channel interface is configured for SPAN.
- B. The Fibre Channel interface is configured for source distribution.
- C. The Fibre Channel interlace is configured for FSPF.
- D. The Fibre Channel interface is configured for synchronization distribution.

Answer: A

QUESTION 13

Which two methods are available to manage an ACI REST API session authentication when a user is unauthenticated? (Choose two.)

- A. POST to aaaUserLogin
- B. GET to aaaListDomains
- C. GET aaaRefresh
- D. DELETE to aaaLogout
- E. POST to aaaLogin

Answer: CE

QUESTION 14

A customer has a requirement for an automation solution that supports periodically acquiring configuration from a centralized server and aligning UCS servers to their desired state.

Which open-source tool meets this requirement?

- A. SaltStack
- B. Kubernetes
- C. Puppet
- D. Terraform

Answer: C

QUESTION 15

An administrator needs to configure an automated policy to shut down a link when a given threshold is exceeded on MDS switch.

Which feature needs to be used?

- A. RMON
- B. EEM
- C. Call Home
- D. Scheduler

Answer: B