

➤ **Vendor: Cisco**

➤ **Exam Code: 350-601**

➤ **Exam Name: Implementing and Operating Cisco Data Center Core Technologies (DCCOR)**

➤ **New Updated Questions from [Braindump2go](#) (Updated in [Sep/2020](#))**

[Visit Braindump2go and Download Full Version 350-601 Exam Dumps](#)

QUESTION 50

Which two statements about multicast routing are true? (choose two)

- A. You can define RPF routes for multicast when you want multicast data to diverge from the unicast traffic path
- B. Multicast routes are used to directly forward traffic without making RPF checks
- C. You can define RPF routes for multicast on border routers to enable reverse path forwarding to an external network
- D. RPF routes for multicast can be distributed
- E. IPv6 static multicast routes are supported

Answer: AC

QUESTION 51

Which three options are benefits of the vPC peers switch feature? (Choose 3)

- A. It eliminates the recommendation to pin the STP root to the vPC primary switch.
- B. It allows a pair of the vPC peer devices to appear as a single STP root in the Layer 2.
- C. After the peer link comes up, it performs an ARP bulk sync over CFSOE to the peer switch.
- D. It improves convergences for Layer 3 flows.
- E. It simplifies STP configuration by configuration both vPCs with the same STP priority.

Answer: ABE

QUESTION 52

Which two settings must be configured before enabling a Cisco UCS Manager domain for Cisco Intersight connectivity? (Choose two.)

- A. SMTP servers
- B. SMTP reply-to address
- C. NTP servers
- D. syslog redirection
- E. DNS servers

Answer: CE

QUESTION 53

An engineer must configure Cisco IMC server management NIC for autonegotiation. Which setting should be selected?

[350-601 Exam Dumps](#) **[350-601 Exam Questions](#)** **[350-601 PDF Dumps](#)** **[350-601 VCE Dumps](#)**

<https://www.braindump2go.com/350-601.html>

- A. shared LOM
- B. Cisco card
- C. dedicated
- D. shared LOM EXT

Answer: C

QUESTION 54

A network engineer is adding a Cisco HyperFlex data platform to the Cisco Intersight management portal. Which two components are required for Intersight to claim the Cisco HyperFlex data platform? (Choose two.)

- A. device FQDN
- B. device claim code
- C. device public IP address
- D. device ID
- E. device serial number

Answer: BD

QUESTION 55

Where is the witness deployed in a two-node Cisco HyperFlex Edge deployment?

- A. to the HyperFlex Edge two-node cluster
- B. to Cisco Intersight
- C. to a third-party cloud provider
- D. to an additional server with network access to HyperFlex Edge

Answer: B

QUESTION 56

Refer to the exhibit. What is the result of this series of commands?

```
UCS-A# scope adapter 1/1/1
UCS-A# /chassis/server/adapter # show image
Name                               Type      Version    State
-----
ucs-m81kr-vic.2.2.1b.bin           Adapter   2.2(1b)    Active

UCS-A# /chassis/server/adapter # update firmware 2.2(1b)
UCS-A# /chassis/server/adapter* # activate firmware 2.2(1b)
set-startup-only
UCS-A# /chassis/server/adapter* # commit-buffer
UCS-A# /chassis/server/adapter #
```

- A. It reboots the server immediately.
- B. It activates the firmware on the next adapter boot.
- C. It updates the firmware on adapter 1/1/1 immediately.
- D. It verifies the firmware update on the server.

Answer: B

QUESTION 57

What is the benefit of adding Cisco HyperFlex Hardware Acceleration Cards to a HyperFlex deployment?

- A. increased compression efficiency
- B. increased network throughput
- C. GPU acceleration
- D. offline encryption acceleration

Answer: A

QUESTION 58

When the default firmware package is set to a new version, which type of policy determines the limiting of server reboots during the firmware upgrade?

- A. diagnostics
- B. maintenance
- C. local disk
- D. BIOS

Answer: B

QUESTION 59

Which two hypervisors does Cisco HyperFlex support? (Choose two.)

- A. OpenStack
- B. Citrix XenServer
- C. VMware vSphere
- D. RedHat KVM
- E. Microsoft Hyper-V

Answer: CE

QUESTION 60

An engineer changed a configuration and must perform a rollback. Which statement applies to a Cisco Nexus 5600 Series Switch?

- A. The configuration rollback functionality is disabled when FCoE is enabled.
- B. A system checkpoint is generated automatically when the running configuration is saved to NVRAM.
- C. A user who is assigned to the network-operator user role can perform a rollback.
- D. Errors are skipped when an atomic rollback type is triggered.

Answer: A

QUESTION 61

Which statement about the impact of a rolling EPLD upgrade on a Cisco MDS 9000 Series Switch is true?

- A. The upgrade can be performed from the standby supervisor module.
- B. Only the modules that are being upgraded are disrupted.
- C. All modules on the switch are disrupted.
- D. An EPLD upgrade is nondisruptive.

Answer: B