

➤ **Vendor: Cisco**➤ **Exam Code: 350-801**➤ **Exam Name: Implementing and Operating Cisco Collaboration Core Technologies (CLCOR)**➤ **New Updated Questions from [Braindump2go](#) (Updated in [September/2020](#))****Visit Braindump2go and Download Full Version 350-801 Exam Dumps****QUESTION 40**

Drag and Drop Question

According to the QoS Baseline Model, drag and drop the applications from the left onto the correct per-Hop Behavior values on the right.

voice	AF11
interactive video	CS2
bulk data	EF
call-signaling	AF31/CS3
network management	AF41

Answer:

bulk data
network management
voice
call-signaling
interactive video

Explanation:

https://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/WAN_and_MAN/QoS_SRND/QoS-SRND-Book/QoSIntro.html

[350-801 Exam Dumps](#) [350-801 Exam Questions](#) [350-801 PDF Dumps](#) [350-801 VCE Dumps](#)**<https://www.braindump2go.com/350-801.html>**

QUESTION 41

Refer to the exhibit. Which option describes the security encryption status of this active call on a Cisco IP phone?



- A. unencrypted call signaling and media
- B. encrypted call signaling but unencrypted call media
- C. encrypted call media but unencrypted call signaling
- D. encrypted call signaling and media
- E. Not enough information provided to answer this question.

Answer: D

QUESTION 42

Which design restriction applies to Cisco Unified Communications Manager Session Management Edition clustering over the WAN deployment with extended round-trip times in Cisco Unified CM 9.1 and later releases?

- A. SIP and H.323 intercluster trunks are supported.
- B. Only SIP trunk is supported.
- C. SIP trunks and H.323 gateways are supported.
- D. A minimum of 1.544 Mb/s bandwidth is required for all traffic between any two nodes in the cluster.
- E. Only RSVP agents can be configured and registered to the SME cluster as media resources.

Answer: B

QUESTION 43

An administrator is trying to change the default LINECODE for a voice ISDN T1 PRI. Which command makes the change?

- A. linecode ami
- B. linecode hdb3
- C. linecode b8zs
- D. linecode esf

Answer: A

Explanation:

https://www.cisco.com/en/US/docs/ios/dial/configuration/guide/dia_cfg_isdn_pri_external_docbase_0900e4b1806c752c_4container_external_docbase_0900e4b18216dd1b.html

QUESTION 44

How does an administrator make Cisco IP phone display the last 10 digits of the calling number when the call is in the connected state, and also display the calling number in the E.164 format within call history on the phone?

- A. Configure a calling party transformation pattern that keeps only last 10 digits.
- B. Configure a translation pattern that has a calling Party Transform Mask of XXXXXXXXXX.
- C. On the inbound SIP trunk, change Significant Digits to 10.
- D. Change the service parameter Apply Transformations On Remote Number to True.

Answer: D

QUESTION 45

[350-801 Exam Dumps](#) [350-801 Exam Questions](#) [350-801 PDF Dumps](#) [350-801 VCE Dumps](#)

<https://www.braindump2go.com/350-801.html>

Which configuration tells a switch port to send Cisco Discovery protocol packets that configure an attached Cisco IP phone to trust tagged traffic that is received from a device that is connected to the access port on the Cisco IP phone?

- A. Router# configure terminal
Router(config)# interface gigabitethernet 5/1
Router(config-if)# platform qos trust extend
- B. Router# configure terminal
Router(config)# interface gigabitethernet 5/1
Router(config-if)# platform qos trust extend cos 3
- C. Router# configure terminal
Router(config)# interface gigabitethernet 5/1
Router(config-if)# platform qos trust extend cos 5
- D. Router# configure terminal
Router(config)# interface gigabitethernet 5/1
Router(config-if)# platform qos extend trust

Answer: A

QUESTION 46

An engineer configures Cisco Unified Communications Manager to prevent toll fraud. At which two point does the engineer block the pattern in Cisco Unified CM to complete this task? (Choose two.)

- A. route pattern
- B. translation pattern
- C. route group
- D. partition
- E. CSS

Answer: DE

QUESTION 47

What is a software-based media resource that is provided by the Cisco IP Voice Streaming Application?

- A. Video conference bridge
- B. transcoder
- C. annunciator
- D. auto-attendant

Answer: C

Explanation:

https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/srnd/collab09/clb09/media.html

QUESTION 48

Multiple router patterns match a number. How does Cisco Unified Communications Manager determine which pattern to use?

- A. the one that discards everything PreDot
- B. the one with the longest match
- C. the one that comes first in numerical order
- D. the one with the closest match

Answer: D

Explanation:

<https://www.cisco.com/c/en/us/support/docs/voice-unified-communications/unified-communications-manager-callmanager/13920-call-routing.html#bcr>

QUESTION 49

A user forwards a corporate number to an international number.
What are two methods to prevent this forwarded call? (Choose two.)

- A. Configure all forced code on all router.
- B. Block international dial patterns in the SIP trunk CSS.
- C. Configure a Forced Authorization Code on the international router pattern.
- D. Set the call Classification to OnNet for the international route pattern.
- E. Set call forward All CSS to restrict international dial patterns.

Answer: CE

Explanation:

https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucme/admin/configuration/manual/cmeadm/cmetrans.html

QUESTION 50

An administrator recently upgraded a Cisco Webex DX80 through its web interface but discovered the next morning that the unit had reverted to its previous version. What must the administrator do to prevent this from happening again?

- A. Confirm the phone load name in the phone configuration.
- B. Set the prepare cluster for rollback to pre-8.0 enterprise parameter to true.
- C. Assign a universal device template to the phone.
- D. Assign a phone security profile with secure SIP.

Answer: A

QUESTION 51

When a phone is registered over Mobile and Remote Access, where does it register?

- A. Expressway-C
- B. Cisco Unified Communications Manager
- C. Cisco Unified presence server
- D. Expressway-E

Answer: B

Explanation:

https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/12_0_1/systemConfig/cucm_b_system-configuration-guide-1201/cucm_b_system-configuration-guide-1201_chapter_01011010.html

QUESTION 52

A network administrator deleted a user from the LDAP directory of a company. The end user shows as Inactive LDAP Synchronize User in Cisco Unified Communications Manager. Which step is next to remove this user from Cisco Unified Communications Manager?

- A. Restart the Dirsync service after the user is deleted from LDAP directory.
- B. Delete the user directly from Cisco Unified Communications Manager.
- C. Wait 24 hours for the garbage collector to remove the user.
- D. Execute a manual sync to refresh the local databased and delete the end user.

Answer: C