

➤ **Vendor:** Dell-EMC

➤ **Exam Code:** E20-393

➤ **Exam Name:** Unity Solutions Specialist Exam for Implementation Engineers

➤ **New Updated Questions from [Braindump2go](#) (Updated in [June/2020](#))**

Visit Braindump2go and Download Full Version E20-393 Exam Dumps

QUESTION 267

A Storage administrator would like to increase the capacity of the FAST Cache by 400 GB. The current configuration consists of two 400 GB SAS Flash 2 drives.

Which solution should be recommended for expanding the FAST Cache?

- A. Two 200 GB SAS Flash 2 drives
- B. Two 400 GB SAS Flash 2 drives
- C. Four 200 GB SAS Flash 3 drives
- D. One 400 GB SAS Flash 2 drive

Answer: A

QUESTION 268

Which UEM/CLI command is used to verify the FC ports designated as synchronous on the SPs?

- A. /remote/sys show -fc
- B. /remote/sys show -detail
- C. /remote/sys show -summary
- D. /remote/sys show -sp

Answer: B

QUESTION 269

What is the granularity of FAST VP when relocating data in the pool?

- A. 128 MB
- B. 256 MB
- C. 512 MB
- D. 1024 MB

Answer: B

QUESTION 270

According to best practices, what is the maximum latency of the link between local and remote systems when using synchronous replication?

- A. 5 ms
- B. 10 ms
- C. 20 ms
- D. 40 ms

[E20-393 Exam Dumps](#) [E20-393 Exam Questions](#) [E20-393 PDF Dumps](#) [E20-393 VCE Dumps](#)

<https://www.braindump2go.com/e20-393.html>

Answer: B

QUESTION 271

What is the minimum requirement for a server to boot from a Dell EMC Unity XT storage system via iSCSI?

- A. Hardware iSCSI HBA
- B. TOE NIC
- C. Software iSCSI
- D. iSCSI Initiator

Answer: D

QUESTION 272

What is maximum amount of time allowed when saving a configuration from the Collect Service Information menu from Unisphere in order to avoid a time-out?

- A. 45 minutes
- B. 60 minutes
- C. 90 minutes
- D. 120 minutes

Answer: B

QUESTION 273

What is the default setting of Advanced Deduplication when Data Reduction is selected within Unisphere?

- A. Disabled for thick LUNs and enabled for thin LUNs
- B. Disabled for thin LUNs in an All-Flash pool
- C. Enabled for thin LUNs in an All-Flash pool
- D. Enabled for both thick and thin LUNs

Answer: C

QUESTION 274

What is a consideration when specifying a Dial Home suppression time for a Dell EMC Unity XT storage array?

- A. Can be lengthened or shortened
- B. The time zone where the array is located
- C. Should be set between 1 and 32 hours
- D. Can be enabled at any time

Answer: C

QUESTION 275

A storage administrator configured a Hybrid Dell EMC Unity XT storage system using one default port containing three disk types. They need additional Flash capacity.

What is the correct way to expand the pool?

- A. Add a RAID Group of SAS Flash 4 drives to the pool
- B. Add 2 SAS Flash drives to the FAST Cache
- C. Add 1 SAS Flash drive to the pool
- D. Add a RAID Group of SAS Flash drives to the pool

Answer: A

QUESTION 276

What storage resources can be provisioned to a host that is connected to a Dell EMC Unity XT storage system via Fibre Channel?

- A. LUNs, CIFS shares, and Consistency Group LUNs
- B. VMFS datastores, NFS datastores, and VVol(file) datastores
- C. LUNs, Consistency Group LUNs, and NFS datastores
- D. Consistency Group LUNs, VMFS datastores, and VVol (block) datastores

Answer: B

QUESTION 277

The preferred production interface is active. What does the Dell EMC Unity XT system do once a NAS Server starts outbound traffic to an external service?

- A. Selects interfaces based on advanced static routes
- B. Uses Packet Reflect for outbound communication
- C. Uses the active production interface
- D. Selects the shortest path available

Answer: C

QUESTION 278

A company has a VMware host installed with FC HBAs that is connected to a Dell EMC Unity XT storage array. A 500 GB LUN is provisioned to this host from the Unity array and is in production. The VMware administrator has configured a new vSwitch with the NICs on the server intended for iSCSI traffic. The storage administrator is asked to configure software iSCSI and provision a new 1 TB LUN from the storage array via iSCSI.

What is a consideration when satisfying this request?

- A. A connection must be established between the host iSCSI initiators and Unity iSCSI targets before provisioning the new LUN
- B. Any single host should connect to any single array using one protocol only
- C. The iSCSI configuration must use all the NIC connections to the host
- D. Two iSCSI target interfaces must be configured with IP addresses from separate subnets

Answer: D