

> Vendor: Fortinet

> Exam Code: NS0-593

- Exam Name: NetApp Certified Support Engineer ONTAP Specialist
 - **▶ New Updated Questions from** <u>Braindump2go</u>
 - **→ (Updated in October/2022)**

<u>Visit Braindump2go and Download Full Version NSE5_EDR-5.0</u> <u>Exam Dumps</u>

Question: 21		
MCC-A::> metrocluster show		
Configuration: IP-fabric		
Cluster	Entry Name	State
Local: MCC-A		
	Configuration State	
		awitchover
Remote: MCC-B	AUSO Failure Domain	auso-disabled
	Configuration State	configured
	Mode	waiting-for-switchback
	AUSO Failure Domain	auso-disabled

Referring to the exhibit, what do you need to do to return the MetroCluster to a normal state?

- A. Enterthe metroclustors witch back command on Site B.
- B. Enterthe metrocluster switch back command on Site A.
- C. Enter the storage failover give back command on Site B.
- D. Enter the storage failover give back command on Site A.

	Answer: B	

Question: 22

Your customer mentions that they have accidentally destroyed both root aggregates in their two-node cluster.

In this scenario, what are two actions that must be performed? (Choose two.)

NS0-593 Exam Dumps NS0-593 Exam Questions

NS0-593 PDF Dumps NS0-593 VCE Dumps



- A. Rejoin the second node to the re-created cluster.
- B. Re-createtheclusterfromthelocalbackup.
- C. Install ONTAP from a USB device.

	•
	Answer: A, C
Explanation:	
Overtions 22	
Question: 23	

You have recently discovered that NetApp ONTAP Cloud Manager is not sending AutoSupport messages to NetApp.

In this scenario, what would solve this Issue?

NS0-593 Exam Dumps NS0-593 Exam Questions

NS0-593 PDF Dumps NS0-593 VCE Dumps



- A. Verify that your AWS credentials are correctly added to Cloud Manager. $B.\ Verify that your Net App Support site credentials are correctly added to Cloud Manager.$ C. Verify that your data LIFs allow traffic to mysupport.netapp.com on port 443. D. Verify that the inbound and outbound rules allow AutoSupport on port 80. Answer: C **Explanation:** Question: 24 Your customer calls you because one application is not able to access a NetApp ONTAPS3 bucket. While reviewing the EMS log on the cluster, you see the following message: Thu Jun 24 15:02:47 -0400 [node-01: kernel: nblade.css.s3.AccessDenied:error]: Access is denied for user 'anonymous user' (Vserver 50), from client IP 10.10.10.10 accessing resource '/offload-target'. The same credentials work in another application. In this scenario, what would cause this problem? A. The application is trying to log in as an anonymous user. B. The application is using v2 signatures. C. The application is using v4 signatures. D. The application is trying to access using the HTTP protocol. Answer: A **Explanation:** Question: 25 You Just used the CLI to create a NetApp ONTAP FlexGroup Volume on a NetApp Cloud Volumes ONTAP instance. After creation, you notice odd behavior in NetApp Cloud Manager. In this scenario, what Is the reason for this behavior?
- A. Cloud Volumes ONTAP does not support Flex Group volumes.
- $B.\ The\ Capacity\ Management\ Mode\ within\ Cloud\ Manager\ should\ be\ set\ to\ Manual.$
- C. The Capacity Management Mode within Cloud Manager should be set to Automatic.
- D. Cloud Manager must be used to provision the FlexGroup volume.

Answer: D	
Answer: D	

Explanation:

Question: 26

NS0-593 Exam Dumps NS0-593 Exam Questions

NS0-593 PDF Dumps NS0-593 VCE Dumps



You have a 2-node NetApp FAS2750 switchless cluster with twenty-four 1.8 TB disks that is experiencing performance issues. Upon investigation, you discover several type B consistency points.

NS0-593 Exam Dumps NS0-593 Exam Questions
NS0-593 PDF Dumps NS0-593 VCE Dumps



ati.	325	0.59	2000	Vetter	Set	15/4	tint.	46/4	Sept.	13/x	Carbs	Cooks	- 22	CF 25	27 Jts	Size.	27923	222	ESCRI.	508	2574	- 23
					in	out	2545	weater	good.	orden	309	har	tim	10-2-1-0 2-0-1-1	bermant.	494.5				25	900	
878	. 12	15	1.2	240	30299	341		12215	4		190	11004	12274	5-0-0-0-0-0-0-0-1	5-0-0-2	1004	960	- 5				
	. 6	1	- 1	7	- 1		1995	59195	5 00		150	1805	5009	(0-0-0-1	1006	- 6	- 3	1 1	1.0	- 6	
229	- 10	225	1.0	201	31955	224	2323	23173			2000	25%	2103	\$-1-0-0-0-1-0-0-0	desperate a	226		- 3	1 1			
428		\$12		707	20224	405	3	7075	5 18		100	56%	2129	5-1-2-0-1-1-1-1	2-9-1-7	1008		- 3	1.		- 0:	
575		355		361	24747	347		3349			260	959	1000	3-3-3-0-0-0-0-0-0	4-3-4-1	1,008	*	- 3	1			
184 124 124 124 124 124 124		258	1.0	257	22856	115		3500	- 4		767	597	1993	3-1-2-0-0-1-1-1	8-9-8-3	1005	13	- 5	10		- 6	
285		1	1.0	1	2406	162	304	45500		- 1	250	594	0005	\$100 per \$10	Section 1-2	1,994		- 5	1.			
166				28	1	4	2733	63739	5 64		290	100%	100	(and and and and and and and	(majoritary)	1004	5.5	- 3	4		- 2	
629	- 2	347	- 2	381	25000	416	500.	1252	2 4		- 100	212	2005	2-2-9-0-1-0-2-1	0-0-1-2	1005	3.8	- 0				
295		421	- 12	20.5	25500	133		2004	S 158		340	355	2005	3-2-4-0-0-0-1-2	0-0-5-0	100%	187	- 0	2			
504 405	- 4	ist	- 5	287	11794	432		2766	100		195	fee	. 905%	\$100 \$100 \$100 \$100 \$100 \$100 \$100 \$100	0-0-0-2	1004		- 3	- 1		- 6	
405	- 4	151	7.0	251	20070	423	235	13435	1.0		>95	- 524	5007	\$100 (mg/mg/mg/mg/mg/mg)	gregories?	100%		- 3	1.	. 9	+	
224		1	- 2	1		17	2000	44.003	3 10	- 1	1.000	2009	2009	0-0-0-0-0-1-1-1	0-0-4-2	Loos		- 3	1			
199	9	- 5		. 0	7.	- 0	207	50107	S 108	1	190	1004	3051	5-0-6-0-6-0-1-L	0-0-0-2	3,005	. 74	- 3	1			
114	1.0	535	1.3	360	TOUR S	904	155	10004	7 4		360	929	10.74	Section in the Section	6-0-1-0	1004	46	- 3		- 4	- 5	

Referring to the exhibit, which corrective action would address these consistency points?

- A. Create additional data LIFs.
- B. Convert the 2-node switchless cluster to a 2-node switched cluster.
- C. Add an additional shelf of twenty-four 1.8 TB disks.
- D. Replace the twenty-four 1.8 TB disks with twelve 4 TB disks.

	Answer: C
Explanation:	
Question: 27	

Acustomer's storage administrator Informs you about the deactivated Automatic Switchover (AUSO) feature on their MetroCluster IP environment.

What Information would you tell your customer in this scenario?

- $A.\ The \,AUSO\,feature\,cannot\,be\,activated\,due\,to\,a\,non-mirrored\,aggregate.$
- B. The AUSO feature is not available in Metrocluster IP installations by design.
- C. Afaulty link automatically deactivated the AUSO feature.
- D. This is a configuration failure, you can activate that feature for the customer.

	Answer: A
nation:	
uestion: 28	

You have a new VMware vSphere cluster with ESXI 7.0U2 hosts. The hosts are connected to a 4-node AFF A400 NetApp ONTAP 9.8 cluster with FC LUNs. You have a requirement to identify and follow I/Osfrom each VM on the shared FC LUN-backed datastores for troubleshooting purposes. In this scenario, which VMware feature Is supported by ONTAP software to accomplish this task?

- A. NetworkI/OControl(NIOC)
- B. Virtual machine ID (VMID)
- C. Storage I/O Control (SIOC)
- D. vSphere Cluster Services (vCLS)

NS0-593 Exam Dumps NS0-593 Exam Questions

NS0-593 PDF Dumps NS0-593 VCE Dumps



NS0-593 Exam Dumps NS0-593 Exam Questions
NS0-593 PDF Dumps NS0-593 VCE Dumps



Your customer installed the shelf firmware for their NS224 shelf over a week ago, and the firmware has not upgraded on shelf 1 module B. The customer wants to know what the next steps would be to get the firmware upgraded after verifying that the shelf firmware is indeed loaded onto the system. Which step would you perform to complete the firmware upgrade?

B. Reseat the disk in Bay 0.	
C. Powercycletheshelf.	
D. Reseat the PSU of the shelf.	
	Answer: C
Explanation:	
Overhiere 20	
Question: 30	
After users start reporting the Inability to create new flies in a CIFS shawafl.dir.size.max logged for the volume of the SVM to which the share point this scenario, which action should you take to solve this issue?	• •
A. Delete unneeded files from the directory.	
B. Move the volume to a different aggregate.	
C. Increase the maximum number of files for the volume.	
D. Increase the maximum directory size for the volume.	
	Answer: C
Explanation:	Answer: C
Explanation: Question: 31	Answer: C
· 	
Question: 31 You have connection Issues from a Linux host to an AFF A400 FC LUN. You the NetApp sanlun command to provide troubleshooting information. Which NetApp software package must be installed on the host? A. Virtual Storage Console	
Question: 31 You have connection Issues from a Linux host to an AFF A400 FC LUN. You the NetApp sanlun command to provide troubleshooting information. Which NetApp software package must be installed on the host? A. Virtual Storage Console B. Inventory Collect Tool	
Question: 31 You have connection Issues from a Linux host to an AFF A400 FC LUN. You the NetApp sanlun command to provide troubleshooting information. Which NetApp software package must be installed on the host? A. Virtual Storage Console	
Question: 31 You have connection Issues from a Linux host to an AFF A400 FC LUN. You the NetApp sanlun command to provide troubleshooting information. Which NetApp software package must be installed on the host? A. Virtual Storage Console B. Inventory Collect Tool C. Host Utilities package	
Question: 31 You have connection Issues from a Linux host to an AFF A400 FC LUN. You the NetApp sanlun command to provide troubleshooting information. Which NetApp software package must be installed on the host? A. Virtual Storage Console B. Inventory Collect Tool C. Host Utilities package	
Question: 31 You have connection Issues from a Linux host to an AFF A400 FC LUN. You the NetApp sanlun command to provide troubleshooting information. Which NetApp software package must be installed on the host? A. Virtual Storage Console B. Inventory Collect Tool C. Host Utilities package	u are asked by support to run
Question: 31 You have connection Issues from a Linux host to an AFF A400 FC LUN. You the NetApp sanlun command to provide troubleshooting information. Which NetApp software package must be installed on the host? A. Virtual Storage Console B. Inventory Collect Tool C. Host Utilities package D. SnapDrivefor UNIX	u are asked by support to run

NS0-593 Exam Dumps NS0-593 Exam Questions

NS0-593 PDF Dumps NS0-593 VCE Dumps



After a normal power down of both nodes for building maintenance, Node01 of a 2-node cluster cannot be powered back up; however, all disk shelves are powered.

NS0-593 Exam Dumps NS0-593 Exam Questions
NS0-593 PDF Dumps NS0-593 VCE Dumps

Which action should be performed to bring the cluster online and allow Node02 to serve data?

- A. Recreate the cluster with the system configuration recovery cluster recreate -from node
- B. Reboot the node With the system node reboot -node Node02 -bypass-optimization true command.
- C. Perform a takeover with the storage failover takeover -ofnode Node01 -option force command.

D. Reinitialize the cluster with option 4a from the boot menu.	
	Answer: A
Explanation:	
Question: 33	
A system panic due to an "L2 watchdog timeout hard reset" erro message in the SP log.	r occurred. You have found a FIFO
Which FIFO message Is useful for Investigating this Issue?	
A. before NMI BBSP:C=00 L=00 FIFO: F3 F2 F1 F0 5 B2 0 0 0 8 A	80 20 E F E3 C0 C2 3 4 6 7 9 9
B. BIOS exit BBSP:C=2F L=20 FIFO: 2 C8 C9 C4 24 4 6 18 7 8 C. before Reset BBSP:C=00 L=00 FIFO:	11
D. ONTAP Shutdown BBSP:C=00 L=2F FIFO:	
	Answer: B
Explanation:	
Question: 34	
An administrator receives the following error message:	

Mon Dec 23 00:20:36 EST [nodeA: wafl_exempt08: wafl.cp.toolong:error]: Aggregate fas 01 DATA AGGR experienced a long CP.

What are two causes for this error? (Choose two.)

- A. There Is excessive SSD load causing the wear leveling to become unbalanced.
- B. A disk is falling.
- C. There is excessive SATA HDD load.
- D. An SSD disk is performing garbage collection to create a dense data layout.

	_	
		Answer: A, C
		Aliswei. A, C
	_	

Explanation:

NS0-593 Exam Dumps NS0-593 Exam Questions

NS0-593 PDF Dumps NS0-593 VCE Dumps

Question: 35

nect. You are using Cisco Nexus 3132Q cluster intercon nect switches.

After expanding a two-node AFF A300 cluster with two AFF A700 nodes, you observe latencies when You just updated to ONTAP data 9.8 software. accessed indirectl In this scenario, what is causing this problem? ٧. The system A. The 10 Gbps to 10 Gbps node run cluster Interconnect is creating -node a speed mismatch. comman B. AFF A300 and AFF A700 node d netstat mixing Is not supported in comman ONTAP9.8 software. d shows C. The AFF A300 Is using an retrans adapter card for the cluster mits and Interconnect, but only packet onboard ports are drops on supported. the LIFs. D. There is an NXOS The AFF A700 firmware mismatch, verify in the Interoperability Matrix nodes (1MTJ for a supported with 40 version. Gbps and the AFF Answer: A A300 Explanation: connect with 10 Gbps to the cluster intercon

NS0-593 Exam Dumps NS0-593 Exam Questions

NS0-593 PDF Dumps NS0-593 VCE Dumps